Wead Office Library Copy

COMMONWEALTH OF AUSTRALIA Tile 6x/1050, Pt. 2

Folio 9

DEPARTMENT OF NATIONAL DEVELOPMENT

BUREAU OF MINERAL RESOURCES, GEOLOGY AND GEOPHYSICS

RECORD No. 1965/32

MAPS SHOWING THE RESULTS OF AN AIRBORNE MAGNETIC AND RADIOMETRIC SURVEY OF THE BOORABBIN 1: 250,000 AREA,

W A 1957

060342





Map Nos.

G 334 - 6

G 334 - 7

G 334 - 8

G 334 - 9

Scale 1:126,720

The information contained in this report has been obtained by the Department of National Development as part of the policy of the Commonwealth Government to assist in the exploration and development of mineral resources. It may not be published in any form or used in a company prospectus or statement without the permission in writing of the Director, Bureau of Mineral Resources, Geology and Geophysics.

COMMONWEALTH OF AUSTRALIA

DEPARTMENT OF NATIONAL DEVELOPMENT

BUREAU OF MINERAL RESOURCES, GEOLOGY AND GEOPHYSICS

RECORD No. 1965/32


MAPS SHOWING THE RESULTS OF AN AIRBORNE MAGNETIC AND RADIOMETRIC SURVEY OF THE BOORABBIN 1: 250,000 AREA,


W A 1957

Map Nos. G 334 - 6 G 334 - 7 G 334 - 8 G 334 - 9

Scale 1:126,720

The information contained in this report has been obtained by the Department of National Development as part of the policy of the Commonwealth Government to assist in the exploration and development of mineral resources. It may not be published in any form or used in a company prospectus or statement without the permission in writing of the Director, Bureau of Mineral Resources, Geology and Geophysics.







MAP DATA PROJECTION:- Transverse Mercator Australian Series CONTROL & DETAIL: After Western Australian Department of Lands and Surveys RELIABILITY:- Planimetric detail: Accurate Flight lines: Accuracy is generally within 100 yards.

TOTAL MAGNETIC INTENSITY MEASURED BY AIRBORNE MAGNETOMETER AND

MAP SHOWING

RADIOMETRIC ANOMALIES DETECTED BY AIRBORNE SCINTILLOGRAPH





_____ Contour/Flight line intersections




This map was compiled from an airborne survey of the Boorabhin 4-mile area flown by the Bureau of Mineral Resources between May and July 1959. The objects of the survey were (a) to delineate magnetic anomalies which might be associated with mineral deposits or reveal structural trends in the geology of the area and (b) to indicate areas in which uranium minerals might occur, and (c) to record changes in the level of radioactive intensity, as an aid to geological mapping.

The survey was made with a D C.3 aircraft at an altitude of 500 feet above ground level along lines spaced one mile apart. The height of the aircraft was controlled through a radio altimeter. Aerial photographs were used for navigation and the actual course of the aircraft was recorded by a 35-mm camera operated during flight.

The total magnetic intensity was recorded continuously by an airborne magnetometer. The data remain uncorrected for a regional gradient in total magnetic field of 7.5 gammas per mile in a direction 5.5° E.

The gamma radiation from the ground was recorded continuously by an airborne scintillograph. No claim is made that the radiometric anomalies correspond to uranium deposits. Investigation on the ground would be necessary to determine the importance of the anomalies.




MAGNETIC CONTOUR INTERVAL 50 GAMMAS

S.E G 334-9

DEPARTMENT OF NATIONAL DEVELOPMENT. BUREAU OF MINERAL RESOURCES, GEOLOGY AND GEOPHYSICS COMPILED AND DRAWN IN THE GEOPHYSICAL BRANCH. MELBOURNE ____ Magnetic Low

____ Contour/Flight line intersections





DEPARTMENT OF NATIONAL DEVELOPMENT. BUREAU OF MINERAL RESOURCES, GEOLOGY AND GEOPHYSICS COMPILED AND DRAWN IN THE GEOPHYSICAL BRANCH. MELBOURNE

MAP SHOWING MAP DATA PROJECTION: - Transverse Mercator Australian Series CONTROL & DETAIL :-After Western Australian Department of Lands and Surveys

RELIABILITY:- Planimetric detail: Accuracy is generally within 100 yards.


> DETECTED BY AIRBORNE SCINTILLOGRAPH SCALE 10 KILOMETRES MAGNETIC CONTOUR INTERVAL 50 GAMMAS

TOTAL MAGNETIC INTENSITY

MEASURED BY AIRBORNE MAGNETOMETER

AND

RADIOMETRIC ANOMALIES



SCINTILLOGRAPH DATA

LEGEND

TOPOGRAPHICAL DATA

EXPLANATORY NOTES


This map was compiled from an airborne survey of the Boorabbin 4-mile area flown by the Bureau of Mineral Resources between May and July 1959. The objects of the survey were (a) to delineate magnetic anomalies which might be associated with mineral deposits or reveal structural trends in the geology of the area and (b) to indicate areas in which uranium minerals might occur, and (c) to record changes in the level of radioactive intensity, as an aid to geological mapping.

The survey was made with a D C.3 aircraft at an altitude of 500 feet above ground level along lines spaced one mile apart. The height of the aircraft was controlled through a radio altimeter. Aerial photographs were used for navigation and the actual course of the aircraft was recorded by a 35-mm camera operated

The total magnetic intensity was recorded continuously by an airborne magnetometer. The data remain uncorrected for a regional gradient in total magnetic field of 7.5 gammas per mile in a direction 5.5° E.

The gamma radiation from the ground was recorded is made that the radiometric anomalies correspond to uranium deposits. Investigation on the ground would be necessary to determine the importance of the anomalies.






PROJECTION:- Transverse Mercator Australian Series CONTROL & DETAIL: After Western Australian Department of Lands and Surveys RELIABILITY:- Planimetric detail: Accurate Flight lines: Accuracy is generally within 100 yards.


TOTAL MAGNETIC INTENSITY

MEASURED BY AIRBORNE MAGNETOMETER

AND

RADIOMETRIC ANOMALIES





LEGEND

EXPLANATORY NOTES

This map was compiled from an airborne survey of the Boorabbin 4-mile area flown by the Bureau of Mineral Resources between May and July 1959. The objects of the survey were (a) to delineate magnetic anomalies which might be associated with mineral deposits or reveal structural trends in the geology of the area and (b) to indicate areas in which uranium minerals might occur, and (c) to record changes in the level of radioactive intensity, as an aid to geological mapping.

The survey was made with a D.C.3 aircraft at an altitude of 500 feet above ground level along lines spaced one mile apart. The height of the aircraft was controlled through a radio altimeter. Aerial photographs were used for navigation and the actual course of the aircraft was recorded by a 35-mm camera operated during flight.

The total magnetic intensity was recorded continuously by an airborne magnetometer. The data remain uncorrected for a regional gradient in total magnetic field of 7.5 gammas per mile in a direction S.5° E.

The gamma radiation from the ground was recorded continuously by an airborne scintillograph. No claim is made that the radiometric anomalies correspond to uranium deposits. Investigation on the ground would be necessary to determine the importance of the anomalies.