HYDROGEOLOGY OF AUSTRALIA

1987

Scale 1 : 5 000 000

0 200 400 600

KILOMETRES

Simple Conic Projection with Standard Parallels 18°S and 36°S

Published by the Bureau of Mineral Resources, Geology and Geophysics, Department of Resources and Energy in association with the Australian Water Resources Council, issued under the authority of the Minister for Resources and Energy. Base map supplied by the Division of National Mapping, Department of Resources and Energy.

© Commonwealth of Australia 1987

Compiled 1984–6 by G.Jacobson and J.E.Lau with contributions by A.D.Allen, T.T.Bestow, D.P.Commander, Geological Survey of Western Australia; C.P.Hazel, L.M.Leach, D.Schmiede, Queensland Water Resources Commission; M.A.Cobb, R.E.Read, F.C.Smith, Geological Survey of South Australia; R.M.Williams, D.R.Woolley, New South Wales Water Resources Commission; P.S.McDonald, F.J.Milne, H.Qureshi, Northern Territory Department of Mines and Energy; C.R.Lawrence, Y.Nahm, Geological Survey of Victoria; M.R.Banks, R.Burgess, Geological Survey of Tasmania; C.M.Brown, W.R.Evans, M.A.Habermehl, J.S.Esdale†, Division of Continental Geology, BMR; J.S.Hancock, Australian Groundwater Consultants Pty Ltd
Edited by G.W.D'Addario, BMR
Cartography by G.A.Young, R.A.Swoboda, J.N.Mason, BMR
Printed by Mercury-Walch, Hobart, Australia

Principal aquifer; type, distribution and productivity

Porous
- Extensive highly productive aquifers
- Extensive aquifers of low–moderate productivity

Fractured or fissured
- Extensive highly productive aquifers
- Extensive aquifers of low–moderate productivity
- Local aquifers, generally low productivity

The principal aquifer produces the best quality water at highest yield from shallowest depth

Principal aquifer; lithology

Sedimentary and low–grade metamorphic rocks
- Undivided
- Limestone

Igneous and medium to high–grade metamorphic rocks
- Undivided
- Granite
- Basalt

Aquifer age and superposition

- Age of principal aquifer is shown by black symbol
- Age of subsidiary aquifer is shown by green symbol
- Principal aquifer overlies subsidiary aquifer
- Principal aquifer underlies subsidiary aquifer
- Boundary of subsidiary aquifer

Aquifer age

MILLION YEARS	PERIOD	ERA
0	Quaternary	CAINOZOIC
1.8	Tertiary	
65	Cretaceous	MESOZOIC
135	Jurassic	
195	Triassic	
225	Permian	PALAEOZOIC
280	Carboniferous	
345	Devonian	
395	Silurian	
435	Ordovician	
500	Cambrian	
570		PROTEROZOIC
1000		
1600		
2500		
3800		ARCHAEAN

Geological features

- Geological boundary
- Fault, section only

Groundwater quality and temperature

- Boundary between fresh and saline groundwater in principal aquifer; 1500 mg/l total dissolved solids isoline, ticks point towards fresh water
- ± 65 Groundwater temperature, degrees Celsius at surface *

Groundwater movement

- 400 Contours on the potentiometric surface, metres above sea level *
- Direction of groundwater flow *
- Limit of main confining bed, ticks point towards confined area *
- Limit of artesian flow *
- Group of springs, average discharge 0–3 million m³/year
- Group of springs, average discharge 3–30 million m³/year
- Groundwater seepage
- 240 Radiometric age of groundwater, thousands of years *
- Groundwater divide *

Surface hydrology

- Perennial stream, average discharge >30 m³/second
- Perennial stream, average discharge <30 m³/second
- Intermittent stream, average discharge >30 m³/second
- Intermittent stream, average discharge <30 m³/second
- Storages, including lakes so used
- Perennial lakes, not used as storages
- Ephemeral lakes, not used as storages

Man–made features and alterations of the groundwater regime

- Borefield, average discharge 1–10 million m³/year
- Borefield, average discharge 10–100 million m³/year
- Borefield, average discharge >100 million m³/year
- Groundwater pipeline
- Artificial recharge site
- Groundwater desalination plant; feedwater capacity >50 000 m³/year
- Pollution of regional aquifer
- Rising water table and salinisation

* In multiaquifer systems, these symbols refer to the basal aquifer of the system

It is recommended that this map be referred to as:
Jacobson, G. & Lau, J. E. (compilers) 1987 – Hydrogeology of Australia (1 : 5 000 000 scale map). Bureau of Mineral Resources, Canberra.

This map is accompanied by a text publication:
Lau, J. E.; Commander, D. P., & Jacobson, G., 1987 – Hydrogeology of Australia. Bureau of Mineral Resources, Australia, Bulletin 227.

PRINCIPAL HYDROGEOLOGICAL DIVISIONS

Fractured rock province
Sedimentary basin
GAB Basin name

Scale 0 200 400 600km

TOPOGRAPHY
Height above sea level
- 1500–2228m
- 1000–1500m
- 500–1000m
- 0–200m
- Below sea level

ANNUAL RAINFALL DEFICIT
Excess of evaporation over rainfall
- > 4000mm
- 3000–4000mm
- 2000–3000mm
- 1000–2000mm
- 0mm (rainfall surplus)
- 401–800mm
- 0–400mm

DRAINAGE AND RUNOFF
Drainage
- External
- Internal
- Once–ordered accidental surface flow
- No surface drainage

Annual runoff
- > 250mm
- 51–250mm
- 0–50mm

GROUNDWATER SALINITY
Total dissolved solids content of principal aquifer
- 0–1500 mg/l
- 1500–5000 mg/l
- > 5000 mg/l

1500 mg/l total dissolved solid isoline, ticks point towards fresh water

Scale 0 200 400 600km

Section V/H = 100