

Department of the Interior
U.S. Geological Survey

**LANDSAT 7 (L7)
ENHANCED THEMATIC MAPPER (ETM+)
LEVEL 1 (L1)
DATA FORMAT CONTROL BOOK (DFCB)**

Version 11.0

April 2007



**LANDSAT 7 (L7)
ENHANCED THEMATIC MAPPER (ETM+)
LEVEL 1 (L1)
DATA FORMAT CONTROL BOOK (DFCB)**

April 2007

Prepared By:

B. Tuscherer Date
LPGS & NLAPS Systems Engineer
SAIC

Reviewed By:

A. Meyerink Date
Landsat A&P Task Lead
SAIC

Concurred By:

S. Labahn Date
Landsat Ground Segment Manager
SAIC

Approved By:

J. Lacasse Date
Landsat Mission Management Officer
U.S. Geological Survey

EROS
Sioux Falls, South Dakota

Executive Summary

This Data Format Control Book (DFCB) presents detailed data formats of the output files generated by the Image Assessment System (IAS), the Level 1 (L1) Product Generation System (LPGS), and the National Land Archive Production System (NLAPS). These L1 processing systems produce L1 output files from Level 0R images based on user requests. Images in the following formats are possible from the various L1 processing systems: Hierarchical Data Format (HDF), FAST-Landsat 7 (FAST-L7A), Geographic Tagged Image File Format (GeoTIFF), or NLAPS Data Format (NDF). IAS and LPGS do not generate products in NDF format. The NLAPS Systematic Format Description Document describes the NDF format (see References).

This Data Format Control Book (DFCB) is maintained and controlled by the Landsat Configuration Control Board (LCCB) and may be updated or revised only on approval by the LCCB. Comments and questions regarding this DFCB should be directed to:

Landsat Mission Management Officer
USGS/EROS
47914 252nd Street
Sioux Falls, SD 57198

Document History

Document Number	Document Version	Publication Date	Change Number
L1-409	Version 4	January 2000	
L7-DFCB-04	Version 5	April 2001	CCR1156, CCR1297, CCR1348, CCR1400, CCR1401, CCR1402, CCR1460, CCR1461
L7-DFCB-04.6	Version 6	April 30, 2004	LCCR0064, LCC00R78, LCCR0096, LCCR0099, LCCR0110, LCCR0111, LCCR0112, LCCR0119, LCCR0136, LCCR0139, LCCR0189, LCCR0190, LCCR0191, LCCR0200, LCCR0204, LCCR0219
L7-DFCB-04.7	Version 7	July 2004	CCR3016, CCR3029
L7-DFCB-04.8	Version 8.0	November 9, 2004	CCR 3625
L7-DFCB-04.9	Version 9.0	September 2, 2005	LCCR 0264, LCCR 0285, LCCR 0286
L7-DFCB-04	Version 10.0	May 1, 2006	CCR 2946, CCR 3654, CCR 3727, CCR 3748, CCR 3833, CCR 3901, CCR 3928, CCR 4152, CCR 4172, CCR 4173, CCR 4174, CCR 4175, CCR 4176, CCR 4275
LS-DFCB-04	Version 11.0	April 2007	LCCR 358

Contents

Executive Summary	iii
Document History	iv
Contents.....	v
List of Tables	vii
Section 1 Introduction.....	1
1.1 Purpose.....	1
1.2 Scope.....	1
1.3 Intended Users.....	1
1.4 Definitions	1
1.5 LORp Pre-Archive Processing.....	4
Section 2 Overview of Level 1 Output Files.....	5
2.1 FAST-L7A	6
2.1.1 Level 1 Image File.....	7
2.1.2 Header File	7
2.1.3 Level 1 Metadata File.....	7
2.1.4 Gap Mask	7
2.2 GeoTIFF.....	8
2.2.1 Level 1 Image File.....	9
2.2.2 Level 1 Metadata File.....	9
2.2.3 Gap Mask	9
2.3 HDF	9
2.3.1 Level 1 Image File.....	10
2.3.2 Level 1 Metadata File.....	11
2.3.3 Ancillary Data Files	11
2.3.4 Gap Mask	11
2.4 NLAPS Data Format (NDF).....	11
2.4.1 Level 1 Image File.....	12
2.4.2 Header File	12
2.4.3 Level 1 Metadata File.....	13
2.4.4 Gap Mask	13
2.4.5 Work Order Report File.....	13
2.4.6 History Processing Parameters File.....	13
2.4.7 DEM Header File (Optional).....	13
2.4.8 DEM Data File (Optional).....	13
Section 3 Level 1 Output File Formats.....	14
3.1 FAST-L7A File Formats	14
3.1.1 Level 1 Image File.....	14
3.1.2 Header File	14
3.1.3 Level 1 Metadata File.....	46
3.1.4 Gap Mask	46
3.2 GeoTIFF File Formats.....	46
3.2.1 Level 1 Image File.....	46
3.2.1.1 GeoTIFF Tags	47

3.2.1.2	GeoTIFF Keys	48
3.2.2	Level 1 Metadata File.....	51
3.2.3	Gap Mask	51
3.3	HDF File Formats.....	52
3.3.1	Level 1 Image File.....	52
3.3.1.1	HDF Directory File	52
3.3.1.2	Vgroup Definitions	52
3.3.2	Level 1 Metadata File.....	54
3.3.3	Ancillary Data Files	84
3.3.3.1	Internal Calibrator (IC) Data Files	84
3.3.3.2	Mirror Scan Correction Data (MSCD) File	85
3.3.3.3	Payload Correction Data (PCD) File	85
3.3.3.4	Scan Line Offsets	85
3.3.3.5	Calibration Parameter File (CPF).....	86
3.3.3.6	Geolocation Table File.....	86
3.3.3.7	LPS Metadata File	86
3.3.4	Gap Mask	86
3.4	NLAPS Data Format (NDF).....	86
3.4.1	Level 1 Image File.....	86
3.4.2	Header File	86
3.4.3	Level 1 Metadata File.....	90
3.4.4	Gap Mask	90
3.4.5	Work Order Report File.....	90
3.4.6	History Processing Parameters File.....	98
3.4.7	DEM Header File (Optional).....	98
3.4.7.1	ETM+ NLAPS DEM Header Example.....	98
3.4.8	DEM Data File (Optional).....	99
Section 4	Product Packaging	100
4.1	Digital Linear Tape (DLT).....	100
4.2	CD-ROM	100
4.3	DVD-R.....	101
4.4	Electronic Transfer	101
Section 5	Software Tools	103
5.1	NCSA HDF Libraries.....	103
5.2	HDF Libraries.....	103
5.3	ODL Parser	104
Appendix A	Projection Parameters	105
References		109

List of Tables

Table 2-1. FAST-L7A Product Components	5
Table 2-2. GeoTIFF Product Components	5
Table 2-3. HDF Product Components	6
Table 2-4. NDF Product Components	6
Table 2-5. FAST-L7A File Naming Convention	7
Table 2-6. Gap Mask File Naming Convention.....	8
Table 2-7. GeoTIFF Product Naming Convention L1 Metadata File.....	9
Table 2-8. HDF Naming Convention	10
Table 2-9. CPF Naming Convention Table.....	10
Table 2-10. NDF Naming Convention	12
Table 3-1. Administrative Record for Panchromatic Band	20
Table 3-2. Radiometric Record for Panchromatic Band	22
Table 3-3. Geometric Record for Panchromatic Band	26
Table 3-4. Administrative Record for VNIR and SWIR Bands	30
Table 3-5. Radiometric Record for VNIR and SWIR Bands	32
Table 3-6. Geometric Record for VNIR and SWIR Bands	36
Table 3-7. Administrative Record for Thermal Bands	40
Table 3-8. Radiometric Record for Thermal Bands	42
Table 3-9. Geometric Record for Thermal Bands	46
Table 3-10. Gap Mask Codes	46
Table 3-11. GeoTIFF Keys	51
Table 3-12. Vgroup Definitions: Level 1R Product	53
Table 3-13. Vgroup Definitions: Level 1G Product	54
Table 3-14. Level 1 Metadata File	84
Table 3-15. Header File Parameters	90
Table A-1. L1G Fast-L7A Projection Parameters	105
Table A-2. USGS Projection Parameters – Projection Transformation Package Projection Parameters.....	106
Table A-3. USGS Projection Parameters - Projection Transformation Package Projection Parameters Elements 9-15.....	107
Table A-4. USGS Projection Parameters Key	108

Section 1 Introduction

1.1 Purpose

This Data Format Control Book (DFCB) provides the user with a high-level description of the Landsat 7 (L7) Level 1 (L1) distribution product, product packaging, and viewing tools.

1.2 Scope

This DFCB describes the formats and data contents of the L1 output files. The formats discussed are Hierarchical Data Format (HDF), FAST-Landsat 7 (FAST-L7A), Geographic Tagged Image File Format (GeoTIFF), and National Land Archive Production System (NLAPS) Data Format (NDF). The NLAPS Precision and Terrain Formats Description Document, at http://edc.usgs.gov/guides/images/landsat_tm/nlapsgeo2.html, also describes NDF specifications.

HDF L1 product formats are derived primarily from Level 0Rp (L0Rp) product formats to cause less impact on the user community and to provide general consistency in output. The Landsat 7 System Zero-R Distribution Product Data Format Control Book, Volume 5, Book 1 (See References) describes L0Rp product formats. (Note: L1 customers are advised to obtain a copy of Book 1 because related tables are referenced in Book 2 to describe L1R output files.) In addition, the output files defined in this DFCB are based on the already established FAST and GeoTIFF standards. The L7 L1 products are in FAST-L7A format. This is the FAST-C format modified to accommodate the features of the Enhanced Thematic Mapper Plus (ETM+) instrument.

The file formats contained in this DFCB are applicable to the product generated by L1 producing systems operated at the U.S. Geological Survey (USGS) Center for Earth Resources Observation and Science (EROS).

1.3 Intended Users

This document is intended as a guide for L1 product recipients. It also provides detailed information on L1 product packaging.

1.4 Definitions

Level 0Rp (L0Rp) digital image—Spatially reformatted, demultiplexed, and unrectified subinterval data

Level 0Rp (L0Rp) product—L0Rp digital image plus radiometric, calibration, spacecraft attitude, and ephemeris data, consisting of the following files in HDF:

- L0Rp digital image (one file per band)
- Internal Calibrator (IC) data—Calibration data file containing all of the calibration data received on a major frame basis subset to the product size ordered

- Mirror Scan Correction Data (MSCD)—Scan direction and error information subset to the product size ordered
- Payload Correction Data (PCD)—Information on spacecraft attitude and ephemeris, including quality indicators for the entire subinterval from which the product is derived
- Metadata—Descriptive information about the L0Rp image and names of appended files associated with the image
- Calibration Parameter File (CPF)—Formatted file containing radiometric and geometric correction parameters
- Scan line offsets—Information on actual starting and ending pixel positions for valid image data on a line-by-line basis
- Geolocation table—File containing scene corner coordinates and product-specific scene line numbers for bands
- HDF directory—File containing all of the pointers, file size information, and data objects required to process the L0Rp product

Level 1R (L1R) digital image—Radiometrically corrected, but not geometrically resampled

Level 1R (L1R) product—L1 product distributed by the Product Distribution System (PDS) to the customer, consisting of the following in HDF:

- L1R digital image (one image file per band)
- IC data—Calibration data file containing all of the calibration data received on a major frame basis subset to the product size ordered
- Consensus MSCD—Scan direction and error information subset to the product size ordered
- Consensus PCD—Information on spacecraft attitude and ephemeris, including quality indicators for the entire subinterval from which the product is derived
- Metadata—Descriptive information about L0 and L1 digital images and names of appended files associated with the images
- CPF—Formatted file containing radiometric and geometric correction parameters
- Scan line offsets—Information on actual starting and ending pixel positions for valid image data on a line-by-line basis
- Geolocation table—File containing scene corner coordinates and product-specific scene line numbers for bands
- HDF directory—File containing all of the pointers, file size information, and data objects required to open and process the L1 product using the HDF library and interface routines

Consensus file—A single file created from the two original files included with the L0Rp product and errors corrected

Level 1G (L1G) digital image—Radiometrically corrected and resampled for geometric correction and registration to a geographic map projection

Level 1G (L1G) product—L1 product distributed by the PDS to the customer that includes, for all requested bands, FAST-L7A, GeoTIFF, or NDF format L1G images and associated data accommodated by the format, or HDF L1G images and metadata

Level 1G gap-filled product—L1 Geometrically Corrected (L1G) gap-filled product that includes radiometric and geometric corrections and SLC-off induced missing pixels filled with mathematically calculated values based on coregistered data (The product includes a gap mask for each band that identifies the source of the fill data on a pixel-by-pixel basis.)

Level 1Gt—Level 1Gt (L1Gt) Terrain Correction product that includes radiometric and geometric corrections and uses a Digital Elevation Model (DEM) to correct parallax error due to local topographic relief (For locations outside of the United States, accuracy of the terrain corrected product depends upon the availability of local Ground Control Points (GCPs), as well as the resolution of the best available DEM.)

Level 1P (L1P)—Includes radiometric and geometric correction and uses GCPs to improve accuracy (For locations outside of the United States, accuracy of the precision-corrected product depends upon the availability of local GCPs. NLAPS processes all L1P products.)

Level 1T (L1T)—Includes radiometric, geometric, and precision correction and uses a DEM to correct parallax error due to local topographic relief (For locations outside of the United States, the accuracy of the terrain-corrected product depends upon the availability of GCPs, as well as the resolution of the best available DEM.)

Level 1T (L1T)—Segmentation Based Gap-fill Product—L1T product that includes radiometric, geometric, and precision corrections, as well as parallax correction for local topographic relief effects (Scan Line Corrector [SLC]-off induced missing pixels are filled with mathematically calculated values based on pixels within segment boundaries generated using coregistered GeoCover data. The accuracy of the terrain-corrected product depends on the accuracy of the GeoCover data set as well as the resolution of the best available DEM for the requested scene.)

Gap Mask—The gap mask files that accompany an L7 ETM+ SLC-off or gap-filled product are bit mask files showing the locations of the image gaps (areas that fall between ETM+ scans) for SLC-off imagery and providing the fill source data for gap-filled imagery. SLC-off and gap-filled products have one gap mask file per band, while segmentation based gap-fill products have only three gap mask files, for the pan, reflective, and thermal bands, respectively.

Interval—Time duration between the start and stop of an imaging operation (observation) of the L7 ETM+ instrument

Subinterval—Segment of time corresponding to a portion of an observation within a single L7 contact period

Worldwide Reference System (WRS) scene—Digital image that covers an area equivalent to one of the 57,784 scene centers (233 paths by 248 rows areas), as defined by the WRS structure

1.5 L0Rp Pre-Archive Processing

A basic knowledge of the pre-archive ground processing enables the user to better understand the L1 product.

The Landsat Ground System (LGS) acquires ETM+ wideband data directly from the L7 spacecraft by way of two 150-megabits-per-second (Mbps) X-band return links. Each X-band data link is separated into two 75-Mbps channels (In-Phase Channel [I] and Quadrature Channel [Q]) and transmits the acquired wideband data over four 75-Mbps LGS output channels to the Landsat Processing System (LPS). The LPS records all wideband data, at real-time rates, into its wideband data stores. An I-Q channel pair represents a complete data set. One channel holds bands 1 through 6 low gain, and the second holds bands 7 and 8 and a high-gain form of band 6.

The LPS retrieves and processes each channel of raw wideband data, at lower than real-time rates, into separate accumulations of Earth image data, calibration data, MSCD, and PCD. Channel accumulations represented by bands 1 through 6-low and 6-high through 8 become formats 1 and 2, respectively. PCD and MSCD are generated twice, once for each format. Their contents should be identical, but they are not guaranteed to be identical.

The LPS spatially reformats Earth imagery and calibration data into Level Zero Reformatted Archive (L0Ra) data. This involves shifting pixels by integer amounts to account for the alternating forward-reverse scanning pattern of the ETM+ sensor, the odd-even detector arrangement within each band, and the detector offsets inherent to the focal plane array engineering design. All LPS OR corrections are reversible; the pixel shift parameters used are documented in the Image Assessment System (IAS) CPF.

During LPS processing, format 1 bands are duplicated, aligned, and used to assess cloud cover content and to generate scene-based browse data. Cloud cover scores are generated on a scene-by-scene and quadrant-by-quadrant basis. Metadata are generated for the entire subinterval and on a scene-by-scene basis. The image data, PCD, MSCD, calibration data, and metadata are structured into HDF for each format and sent to EROS for archiving in subinterval form. The two formats of data are united when an L7 OR product is ordered. The browse files are sent to EROS search-and-order systems separately for use as an online aid to ordering.

Section 2 Overview of Level 1 Output Files

The L1R digital image is very similar to the L0Rp digital image, except that the L1R image data are radiometrically corrected. In addition, the format 1 and format 2 PCD files are combined into one consensus file, as are the format 1 and format 2 MSCD files. The consensus file is a single file created from the two original files included with the L0Rp product, with errors corrected. The L1R product is available in HDF only. The L1T includes radiometric, geometric, and precision correction and uses a DEM to correct parallax error due to local topographic relief. The L1G digital image is radiometrically and geometrically corrected and is available in four format options: FAST-L7A, GeoTIFF, HDF, and NDF.

Note: The L7 ETM+ SLC-off Segmentation-Based Gap-Filled Product options are more limited than other L7 products primarily due to matching the GeoCover data set for generating GCPs and segment maps including:

- Pixel Size: 14.25 m/28.5 m/28.5 m only
- Product Type: L1T only (need to match GeoCover)
- Map Projection: UTM only (need to match GeoCover)
No +/- 1 zone option
- Orientation: NUP only (need to match GeoCover)

Table 2-1 through Table 2-5 detail the L1 product components included in each format. The number of bands that the user orders determines the number of components in a specific product.

Component	L1G	L1Gt	L1P	L1T
L1 image file (for each requested band)	X	X	X	X
Header file (for each requested band group)	X	X	X	X
L1 metadata file (text [.txt] file)	X	X	X	X
Gap mask	SLC-off & Gap-filled	SLC-off & Gap-filled	SLC-off	SLC-off & Gap-filled

Table 2-1. FAST-L7A Product Components

Component	L1G	L1Gt	L1P	L1T
L1 image file (for each requested band)	X	X	X	X
L1 metadata file (text (.txt) file)	X	X	X	X
Gap mask	SLC-off & Gap-filled	SLC-off & Gap-filled	SLC-off	SLC-off & Gap-filled

Table 2-2. GeoTIFF Product Components

Component	L1R	L1G	L1Gt	L1P	L1T
L1 image file (for each requested band)	X	X	X	X	X
IC data—format 1 (for bands 1 through 6-low)	X				
IC data—format 2 (for bands 6-high through 8)	X				
Scan line offsets—format 1 (for bands 1 through 6-low)	X				
Scan line offsets—format 2 (for bands 6-high through 8)	X				
MSCD (consensus)	X				
PCD (consensus)	X				
CPF	X				
Metadata file (LPS)—format 1 (text [.txt] file)	X				
Metadata file (LPS)—format 2 (text [.txt] file)	X				
L1 metadata file (text [.txt] file)	X	X	X	X	X
Geolocation table	X				
HDF directory file	X	X	X	X	X
Gap mask		SLC-off & Gap-filled	SLC-off & Gap-filled	SLC-off	SLC-off & Gap-filled

Table 2-3. HDF Product Components

Component	L1G	L1Gt	L1P	L1T
L1 image file (for each requested band)	X	X	X	X
Header file (for each requested band group)	X	X	X	X
L1 metadata file (text [.txt] file)	X	X	X	X
Work order report file	X	X	X	X
History and processing parameters file	X	X	X	X
DEM header file		Optional		Optional
DEM data file		Optional		Optional
Gap mask	SLC-Off & Gap-filled	SLC-Off & Gap-filled	SLC-off	SLC-off

Table 2-4. NDF Product Components

2.1 FAST-L7A

The file naming convention for the FAST-L7A product files is:

L7fpprrr_rrrYYYYMMDD_AAA.FST

L7	=	Landsat 7 mission
f	=	ETM+ format (1 or 2) (data not pertaining to a specific format default to 1)
ppp	=	Product starting path
rrr_rrr	=	Product starting and ending rows
YYYYMMDD	=	Image acquisition date
AAA	=	File type: B10 = Band 1 B20 = Band 2 B30 = Band 3 B40 = Band 4 B50 = Band 5 B61 = Band 6L B62 = Band 6H B70 = Band 7 B80 = Band 8 HPN = Panchromatic band header file HRF = VNIR/ SWIR bands header file HTM = Thermal bands header file MTL = L1 metadata
.FST	=	FAST file extension
.txt	=	Only the MTL file ends with .txt (e.g., L7fpppprrr_rrrYYYYMMDD_MTL.txt)

Table 2-5. FAST-L7A File Naming Convention

2.1.1 Level 1 Image File

Each L1 image file contains only one ETM+ band of image pixels. There are no header records within the L1 image file, nor are there prefix or suffix data in the individual image records. Image data are unblocked. The L1 image files are 8-bit unsigned integers.

2.1.2 Header File

The first file that should be read is a Read-Me-First file that contains header data in American Standard Code for Information Interchange (ASCII). Each band group (panchromatic, Visible Near Infrared/Shortwave Infrared [VNIR/SWIR], and thermal) has a specific header file. Alphanumeric fields are left justified and numeric fields are right justified. This file also includes all processing options and map projection information.

2.1.3 Level 1 Metadata File

Please see Section 2.3.2 for L1 Metadata File details.

2.1.4 Gap Mask

The gap mask file is created during product generation and contains the location of all pixels affected by the original SLC-off scene gaps, without any interpolation and/or gap-fill data. The gap masks are 8-bit images that have dimensions identical to the corresponding image band files to simplify data access and viewing. The gap mask uses code 0 to represent no data and codes 1-6 to identify the source image for each filled pixel. Table 3-10 lists the data to which the gap mask codes correspond. Segmentation gap-filled products use only three gap mask files: one for the reflective bands, one for the thermal bands, and one for the panchromatic band. To avoid

expanding the product size dramatically, the gap mask image files are compressed using the GNU zip utility.

The file naming convention for the gap mask files is:

L7Gpppprrr_rrrYYYYMMDD_AAA.TIF.gz

L7	=	Landsat 7 mission
G	=	Gap mask
ppp	=	Product starting path
rrr_rrr	=	Starting and ending rows of the product
YYYYMMDD	=	Image acquisition date
AAA	=	File type: B10 = Band 1 B20 = Band 2 B30 = Band 3 B40 = Band 4 B50 = Band 5 B61 = Band 6L B62 = Band 6H B70 = Band 7 B80 = Band 8 REF = Bands 1-5 and 7 (segmentation gap-filled only) THM = Bands 6L and 6H (segmentation gap-filled only) PAN = Band 8 (segmentation gap-filled only)
.TIF	=	GeoTIFF file extension
.gz	=	GNU zip

Table 2-6. Gap Mask File Naming Convention

2.2 GeoTIFF

The file naming convention for the GeoTIFF product is:

L7fpppprrr_rrrYYYYMMDD_AAA.TIF

L7	=	Landsat 7 mission
f	=	ETM+ format (1 or 2) (data not pertaining to a specific format default to 1)
ppp	=	Product starting path
rrr_rrr	=	Product starting and ending rows
YYYYMMDD	=	Acquisition date of the image
AAA	=	File type: B10 = Band 1 B20 = Band 2 B30 = Band 3 B40 = Band 4 B50 = Band 5 B61 = Band 6L B62 = Band 6H B70 = Band 7 B80 = Band 8 MTL = L1 metadata
.TIF .txt	=	TIF file extension Only the MTL file ends with .txt (e.g., L7fpppprrr_rrrYYYYMMDD_MTL.txt)

Table 2-7. GeoTIFF Product Naming Convention L1 Metadata File

2.2.1 Level 1 Image File

GeoTIFF defines a set of public domain Tagged Image File Format (TIFF) tags that describe all cartographic and geodetic information associated with geographic TIFF imagery. GeoTIFF is a means for tying a raster image to a known model space or map projection and for describing those projections. A metadata format provides geographic information to associate with the image data, but the TIFF file structure allows both the metadata and the image data to be encoded into the same file. The GeoTIFF file is grayscale, scan line, uncompressed, and 8-bit unsigned integers.

2.2.2 Level 1 Metadata File

Please see Section 2.3.2 for L1 Metadata File details.

2.2.3 Gap Mask

Please see Section 2.1.4 for Gap Mask details.

2.3 HDF

The L1R, L1G, L1P, and L1T HDF products are packaged and distributed as a collection of external elements with an HDF directory. External elements are distinguished by the fact that they exist as separate files and contain only data. The HDF directory includes information about the HDF structure and interrelationships. The L1G and L1Gt both share the same extension being L1G.

The file naming convention for the HDF product files (except the CPF) is:

L7fpppprrr_rrrYYYYMMDD_AAA.XXX

L7	=	Landsat 7 mission
f	=	ETM+ format (1 or 2) (data not pertaining to a specific format default to 1)
ppp	=	Product starting path
rrr_rrr	=	Product starting and ending rows
YYYYMMDD	=	Image acquisition date
AAA	=	File type: B10 = Band 1 B20 = Band 2 B30 = Band 3 B40 = Band 4 B50 = Band 5 B61 = Band 6L B62 = Band 6H B70 = Band 7 B80 = Band 8 CAL = Internal calibrator GEO = Geolocation HDF = HDF directory MSD = Consensus MSCD MTA = LPS metadata MTL = L1 metadata PCD = Consensus PCD SLO = Scan line offset
.XXX .txt	=	Product type (L1R, L1G, L1P, or L1T) MTL and MTA files end with .txt (e.g., L7fpppprrr_rrrYYYYMMDD_MTL.txt) <i>Note: The L1G and L1Gt both share the same extension being L1G.</i>

Table 2-8. HDF Naming Convention

The CPF file naming convention is:

L7CPFYYYYMMDD_YYYYMMDD_nn

L7	=	Landsat 7 mission
CPF	=	Calibration parameter file
YYYY	=	Starting year of the CPF
MM	=	Starting month of the CPF
DD	=	Starting day of the CPF
_	=	Separator
YYYY	=	Ending year of the CPF
MM	=	Ending month of the CPF
DD	=	Ending day of the CPF
_	=	Separator
nn	=	01-99

Table 2-9. CPF Naming Convention Table

2.3.1 Level 1 Image File

Each requested image band is self-contained in a single file. The L1R image files are in absolute units scaled to 16 bits. The L1G images are 8-bit unsigned integers that exploit

the full 0-255 numeric range. Note that the L1R image files are constructed on an Intel Linux platform, which is a big-endian byte order machine.

2.3.2 Level 1 Metadata File

The L1 metadata file is created during product generation and contains information specific to the product ordered. This file also contains all applicable image description information from the L0Rp metadata and the LPS L0Ra metadata provided with the L0Rp product. Section 3.3.2 describes this file in detail.

2.3.3 Ancillary Data Files

The remaining files included with the HDF product include the IC data, scan line offsets, MSCD, PCD, CPF, metadata, geolocation table, and HDF directory file. See Table 2-3 for a complete listing of which files are included with each product. Section 3.3.3 describes these files in detail.

2.3.4 Gap Mask

Please see Section 2.1.4 for Gap Mask details.

2.4 NLAPS Data Format (NDF)

The product composition for geometrically and radiometrically corrected Landsat data includes up to eight file types. These types include one or more L1 image files, header files, a work order report file, a Gap Mask, a history and processing parameters file, and some optional DEM header and data files. In Band Sequential (BSQ) format, each band of satellite imagery is stored in a separate file (i.e., scan lines are sequentially written to the same image file).

One or more image header files describe the product delivered and provide necessary information for further processing. One or more image files contain the binary image data. If a DEM is used for terrain correction, a DEM header and DEM image file is included as well, if requested. Also, each NDF product includes a correction processing report file (formerly known as a work order) and a history file indicating processing parameters.

The file naming convention for the NDF product files is:

LE7PPPRRRSSYYDDDMV.XXX

L	=	Landsat		
E	=	ETM+		
7	=	Landsat 7 Mission		
PPP	=	Starting WRS path		
RRR	=	Starting WRS row		
SS	=	00	no shift	WRS row offset (used for "shifted" scenes)
YY	=	Last two digits of acquisition year		
DDD	=	Day of Year (DOY) of acquisition		
M	=	5	ETM+	Instrument mode
V	=	0	multiplexer (MUX)	
.XXX	=	L1 - 1	Band 1	ETM + Band (1-9)
		L1 - 2	Band 2	
		L1 - 3	Band 3	
		L1 - 4	Band 4	
		L1 - 5	Band 5	
		L1 - 6	Band 6, low	
		L1 - 7	Band 7	
		L1 - 8	Band 8	
		L1 - 9	Band 6, high	
		H1	1	Product Header Number
		H1	2	
		H1	3	
		WO	Job Report File	
		HI	Job History File	
		DH	DEM Header	Optional
		DD	DEM Data	Optional
.txt	=	*_MTL.txt	LE7PPPPRRRSSYYDDDMV_MTL.txt	Only the MTL file ends with .txt

Table 2-10. NDF Naming Convention

2.4.1 Level 1 Image File

The L1 image files contain the raw image pixels. There are no header records within the file, nor are there any prefix and/or suffix data to the individual image records. If the L1 image file is part of a BSQ product, then it contains information for only one band, and the image lines for that band are stored sequentially.

2.4.2 Header File

The first file on each volume, a Read-Me-First file, contains header data. It is in ASCII, written to American National Standards Institute (ANSI) and International Standards Organization (ISO) standards. The image header files contain information describing the image data in the image. The header is intended to be easy to read and uses only ASCII-text to represent information (i.e., the header does not contain binary information).

To accommodate multi-resolution products, one header file is written for each resolution in the output product. This is in contrast to previous versions of the NDF format in which all data files in the same volume (data set) were required to have the same pixel spacing and pixel format, with different resolutions requiring a separate volume set.

2.4.3 Level 1 Metadata File

Please see Section 2.3.2 for L1 Metadata File details.

2.4.4 Gap Mask

Please see Section 2.1.4 for Gap Mask details.

2.4.5 Work Order Report File

The Work Order Report file contains information specific to the history and processing parameters used to process the NDF product.

2.4.6 History Processing Parameters File

Each NLAPS data product contains a processing history file. This file provides documentation about the original customer request and the processing parameters used to produce the NLAPS digital product.

2.4.7 DEM Header File (Optional)

The image and DEM header files contain information describing the image data in the image or DEM files. This format is more general than earlier versions of Fast Format headers, but is enhanced by additional sensors, DEM data, and non-satellite imagery information. The header is intended to be easy to read and uses only ASCII-text to represent the information (i.e., the header does not contain binary information).

2.4.8 DEM Data File (Optional)

The image and DEM files contain raw image pixels or elevation samples. There are no header records within the file, nor are there any prefix and/or suffix data to the individual image records. If the image file is part of a BSQ product, then it contains information for only one band, and the image lines for that band are stored sequentially.

Section 3 Level 1 Output File Formats

3.1 FAST-L7A File Formats

3.1.1 Level 1 Image File

Each Earth image band in the requested product is in a separate file. The data are laid out in a scan line sequential format in descending detector order (i.e., detector 16 is followed by detector 15 and so forth for the 30-m bands). The L1R image is radiometrically corrected, but is not geometrically resampled. The L1T image is radiometric, geometric, and precision corrected and uses a DEM to correct parallax error due to local topographic relief. The L1G image is radiometrically corrected and resampled for geometric correction and registration to geographic map projections.

3.1.2 Header File

There is one header file for each band group in the product. The three possible band groups are panchromatic, VNIR/SWIR, and thermal. The header file for each band group contains three 1,536-byte ASCII records: administrative, radiometric, and geometric. The administrative record, the first record in each header file, contains information that identifies the product, the image, and the data specifically needed to ingest the imagery for each particular band. To import the image data, it is necessary to read the entries in the administrative record.

The second record is the radiometric record, which contains the coefficients needed to convert the image digital values into at-satellite spectral radiance for each particular band.

The third record is the geometric record, which contains the image geodetic location information. To align the imagery to other data sources, it is necessary to read the entries in the geometric record for each particular band.

Table 3-1 through Table 3-3 describe the formats of the three records for each of the three band groups (panchromatic, VNIR/SWIR, and thermal). The tables include the start and end bytes, the Fortran format statement, and a brief description of each field. In the Fortran format statements:

A = character data

D = double precision data

F = floating data

All N/A fields are blank filled and are maintained in the records for historical consistency with the FAST-C format. The “b” in the descriptions indicates a space.

Fields 79, 81, 91, and 93 of the administrative record refer to products that span multiple tapes and are, therefore, not applicable to the PDS-distributed L1 products.

Field 106 of the administrative record is the Bands Present field for each particular band group. It is necessary to count the number of non-blank entries in the Bands Present field to get the count of the number of bands. Each character (byte) in this field has an ASCII character with the band label, usually a number. For ETM+, the values are 8 for the panchromatic band; 1, 2, 3, 4, 5, and 7 for the VNIR/SWIR bands; and L and H for the thermal bands. The sequence terminates with blanks.

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	8	A8	REQbIDb=
	2	9	28	A20	Data producer-defined request number that uniquely identifies each product; USGS products use the NNNYYMMDDSSSS_UUUUUU format, where: NNNYYMMDDSSSS = 13-digit Distributed Ordering Research Reporting and Accounting Network (DORRAN) order number NNN = Node indicator YY = Year MM = Month DD = Day SSSS = Sequence number for the day UUUUU = 5-digit DORRAN unit number
	3	29	34	A6	bLOCb=
	4	35	51	A17	First scene starting location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	5	52	70	A19	bACQUISITIONbDATEb=
	6	71	78	A8	First scene acquisition date in yyymmdd format
	7	79	79	1X	Blank fill
	8	80	80	A1	Carriage return
2	9	81	91	A11	SATELLITEb=
	10	92	101	A10	First scene satellite name: LANDSAT7
	11	102	110	A9	bSENSORb=
	12	111	120	A10	First scene sensor name: ETM+
	13	121	134	A14	bSENSORbMODEb=
	14	135	140	A6	First scene sensor mode: NORMAL
	15	141	153	A13	bLOOKbANGLEb=
	16	154	159	F6.2	First scene off-nadir angle in degrees: 0.0
	17	160	160	A1	Carriage return
3	18	161	183	23X	Blank fill
	19	184	194	A11	bLOCATIONb=
	20	195	211	A17	Last scene ending location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	21	212	230	A19	bACQUISITIONbDATEb=
	22	231	238	A8	Last scene acquisition date in yyymmdd format
	23	239	239	1X	Blank fill
	24	240	240	A1	Carriage return
4	25	241	251	A11	SATELLITEb=
	26	252	261	A10	Last scene satellite name: LANDSAT7
	27	262	270	A9	bSENSORb=
	28	271	280	A10	Last scene sensor name: ETM+
	29	281	294	A14	bSENSORbMODEb=
	30	295	300	A6	Last scene sensor mode: NORMAL
	31	301	313	A13	bLOOKbANGLEb=
	32	314	319	F6.2	Last scene off-nadir angle in degrees: 0.0

Line	Field	Start Byte	End Byte	Format	Description
	33	320	320	A1	Carriage return
5	34	321	343	23X	Blank fill
	35	344	354	A11	bLOCATIONb=
	36	355	371	A17	N/A
	37	372	390	A19	bACQUISITIONbDATEb=
	38	391	398	A8	N/A
	39	399	399	1X	Blank fill
	40	400	400	A1	Carriage return
6	41	401	411	A11	SATELLITEb=
	42	412	421	A10	N/A
	43	422	430	A9	bSENSORb=
	44	431	440	A10	N/A
	45	441	454	A14	bSENSORbMODEb=
	46	455	460	A6	N/A
	47	461	473	A13	bLOOKbANGLEb=
	48	474	479	F6.2	N/A
	49	480	480	A1	Carriage return
7	50	481	503	23X	Blank fill
	51	504	514	A11	bLOCATIONb=
	52	515	531	A17	N/A
	53	532	550	A19	bACQUISITIONbDATEb=
	54	551	558	A8	N/A
	55	559	559	1X	Blank fill
	56	560	560	A1	Carriage return
8	57	561	571	A11	SATELLITEb=
	58	572	581	A10	N/A
	59	582	590	A9	bSENSORb=
	60	591	600	A10	N/A
	61	601	614	A14	bSENSORbMODEb=
	62	615	620	A6	N/A
	63	621	633	A13	bLOOKbANGLEb=
	64	634	639	F6.2	N/A
	65	640	640	A1	Carriage return
9	66	641	654	A14	PRODUCTbTYPEb=
	67	655	672	A18	Product type: MAPbORIENTEDbbbbbb ORBITbORIENTEDbbbb USERbORIENTEDbbbb (NLAPS only) TRUENORTHbORIENTED (NLAPS only)
	68	673	687	A15	bPRODUCTbSIZEb=
	69	688	697	A10	Product size: SUBSCENEbb < 375 scans, < 1 scene FULLbSCENE = 375 scans, = 1 scene MULTISCENE > 375 scans, > 1 scene
	70	698	719	22X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	740	A20	TYPEbOFbPROCESSINGb=
	73	741	751	A11	Type of processing used: SYSTEMATICb SYSTERRAINb PRECISIONbb TERRAINbbbb

Line	Field	Start Byte	End Byte	Format	Description
	74	752	764	A13	bRESAMPLINGb=
	75	765	766	A2	Resampling algorithm used: NN = Nearest Neighbor CC = Cubic Convolution MF = Modulation Transfer Function (LPGS only) BI = Bilinear (NLAPS only) KD = Kaiser Damped (NLAPS only) 16 = 16-Point Sinc (NLAPS only) 8b = 8-Point Sinc (NLAPS only) DW = Damped Window (NLAPS only)
	76	767	799	33X	Blank fill
	77	800	800	A1	Carriage return
11	78	801	819	A19	VOLUMEb#/#bINbSETb=
	79	820	821	I2	Tape volume number in tape set (for multi-volume product): N/A
	80	822	822	A1	/
	81	823	824	I2	Number of volumes in tape set (for multi-volume product): N/A
	82	825	842	A18	bPIXELsbPERbLINEb=
	83	843	847	I5	Number of pixels per product line for pan band
	84	848	864	A17	bLINESbPERbBANDb=
	85	865	869	I5	Number of lines per pan band
	87	871	875	I5	Number of lines in output product
	88	876	879	4X	Blank fill
	89	880	880	A1	Carriage return
12	90	881	894	A14	STARTbLINEb#b=
	91	895	899	I5	First product line number on this volume (for multivolume product): N/A
	92	900	917	A18	bBLOCKINGbFACTORb=
	93	918	919	I2	Tape blocking factor: N/A
	94	920	931	A12	bRECbSIZEbb=
	95	932	940	I9	Length of physical file record in bytes per pan band
	96	941	953	A13	bPIXELbSIZEb=
	97	954	959	F6.2	Pixel size in meters for pan band
	98	960	960	A1	Carriage return
13	99	961	983	A23	OUTPUTbBITSbPERbPIXELb=
	100	984	985	I2	Output bits per pixel: 8
	101	986	1011	A26	bACQUIREDbBITSbPERbPIXELb=
	102	1012	1013	I2	Acquired bits per pixel: 8
	103	1014	1039	26X	Blank fill
	104	1040	1040	A1	Carriage return
14	105	1041	1055	A15	BANDSbPRESENTb=
	106	1056	1087	A32	Image bands present for the pan band group: 8
	107	1088	1119	32X	Blank fill
	108	1120	1120	A1	Carriage return
15	109	1121	1130	A10	FILENAMEb=
	110	1131	1159	A29	File name for first band
	111	1160	1169	A10	FILENAMEb=
	112	1170	1198	A29	File name for second band (N/A)
	113	1199	1199	1X	Blank fill
	114	1200	1200	A1	Carriage return
16	115	1201	1210	A10	FILENAMEb=
	116	1211	1239	A29	File name for third band (N/A)
	117	1240	1249	A10	FILENAMEb=
	117	1250	1278	A29	File name for fourth band (N/A)

Line	Field	Start Byte	End Byte	Format	Description
	119	1279	1279	1X	Blank fill
	120	1280	1280	A1	Carriage return
17	121	1281	1290	A10	FILENAMEb=
	122	1291	1319	A29	File name for fifth band (N/A)
	123	1320	1329	A10	FILENAMEb=
	124	1330	1358	A29	File name for sixth band (N/A)
	125	1359	1359	1X	Blank fill
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1532	12X	REVbbbbbbbbb
	132	1533	1535	A3	Format version code: L7A
	133	1536	1536	A1	Carriage return
1	1	1	50	A50	BIASESbANDbGAINSbINbASCENDINGbBANDbNUMBERbORDERbbb
	2	51	79	29X	Blank fill
	3	80	80	A1	Carriage return
2	4	81	104	D24.15	Bias for first band
	5	105	105	1X	Blank fill
	6	106	129	D24.15	Gain for first band
	7	130	159	30X	Blank fill
	8	160	160	A1	Carriage return
3	9	161	184	D24.15	Bias for second band
	10	185	185	1X	Blank fill
	11	186	209	D24.15	Gain for second band
	12	210	239	30X	Blank fill
	13	240	240	A1	Carriage return
4	14	241	264	D24.15	Bias for third band
	15	265	265	1X	Blank fill
	16	266	289	D24.15	Gain for third band
	17	290	319	30X	Blank fill
	18	320	320	A1	Carriage return
5	19	321	344	D24.15	Bias for fourth band
	20	345	345	1X	Blank fill
	21	346	369	D24.15	Gain for fourth band
	22	370	399	30X	Blank fill
	23	400	400	A1	Carriage return
6	24	401	424	D24.15	Bias for fifth band
	25	425	425	1X	Blank fill
	26	426	449	D24.15	Gain for fifth band
	27	450	479	30X	Blank fill
	28	480	480	A1	Carriage return
7	29	481	504	D24.15	Bias for sixth band
	30	505	505	1X	Blank fill
	31	506	529	D24.15	Gain for sixth band
	32	530	559	30X	Blank fill
	33	560	560	A1	Carriage return
8	34	561	584	D24.15	Bias for seventh band
	35	585	585	1X	Blank fill
	36	586	609	D24.15	Gain for seventh band
	37	610	639	30X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	38	640	640	A1	Carriage return
9	39	641	664	D24.15	Bias for eighth band
	40	665	665	1X	Blank fill
	41	666	689	D24.15	Gain for eighth band
	42	690	719	30X	Blank fill
	43	720	720	A1	Carriage return
10	44	721	799	79X	Blank fill
	45	800	800	A1	Carriage return

Table 3-1. Administrative Record for Panchromatic Band

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	50	A50	BIASESbANDbGAINSbINbASCENDINGbBANDbNUMBERbORDERbbb
	2	51	79	29X	Blank fill
	3	80	80	A1	Carriage return
2	4	81	104	D24.15	Bias for first band
	5	105	105	1X	Blank fill
	6	106	129	D24.15	Gain for first band
	7	130	159	30X	Blank fill
	8	160	160	A1	Carriage return
3	9	161	184	D24.15	Bias for second band
	10	185	185	1X	Blank fill
	11	186	209	D24.15	Gain for second band
	12	210	239	30X	Blank fill
	13	240	240	A1	Carriage return
4	14	241	264	D24.15	Bias for third band
	15	265	265	1X	Blank fill
	16	266	289	D24.15	Gain for third band
	17	290	319	30X	Blank fill
	18	320	320	A1	Carriage return
5	19	321	344	D24.15	Bias for fourth band
	20	345	345	1X	Blank fill
	21	346	369	D24.15	Gain for fourth band
	22	370	399	30X	Blank fill
	23	400	400	A1	Carriage return
6	24	401	424	D24.15	Bias for fifth band
	25	425	425	1X	Blank fill
	26	426	449	D24.15	Gain for fifth band
	27	450	479	30X	Blank fill
	28	480	480	A1	Carriage return
7	29	481	504	D24.15	Bias for sixth band
	30	505	505	1X	Blank fill
	31	506	529	D24.15	Gain for sixth band
	32	530	559	30X	Blank fill
	33	560	560	A1	Carriage return
8	34	561	584	D24.15	Bias for seventh band
	35	585	585	1X	Blank fill
	36	586	609	D24.15	Gain for seventh band
	37	610	639	30X	Blank fill
	38	640	640	A1	Carriage return
9	39	641	664	D24.15	Bias for eighth band
	40	665	665	1X	Blank fill
	41	666	689	D24.15	Gain for eighth band
	42	690	719	30X	Blank fill
	43	720	720	A1	Carriage return
10	44	721	799	79X	Blank fill
	45	800	800	A1	Carriage return
11	46	801	879	79X	Blank fill
	47	880	880	A1	Carriage return
12	48	881	959	79X	Blank fill
	49	960	960	A1	Carriage return
13	50	961	1039	79X	Blank fill
	51	1040	1040	A1	Carriage return
14	52	1041	1119	79X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	53	1120	1120	A1	Carriage return
15	54	1121	1199	79X	Blank fill
	55	1200	1200	A1	Carriage return
16	56	1201	1279	79X	Blank fill
	57	1280	1280	A1	Carriage return
17	58	1281	1359	79X	Blank fill
	59	1360	1360	A1	Carriage return
18	60	1361	1439	79X	Blank fill
	61	1440	1440	A1	Carriage return
19	62	1441	1519	79X	Blank fill
	63	1520	1520	A1	Carriage return
20	64	1521	1535	15X	Blank fill
	65	1536	1536	A1	Carriage return

Table 3-2. Radiometric Record for Panchromatic Band

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	14	A14	GEOMETRICbDATA
	2	15	31	A17	bMAPbPROJECTIONb=
	3	32	35	A4	Map projection name (see Appendix A for list of mnemonics)
	4	36	47	A12	bELLIPSOIDb=
	5	48	65	A18	Earth ellipsoid used
	6	66	73	A8	bDATUMB=
	7	74	79	A6	Datum name
	8	80	80	A1	Carriage return
2	9	81	108	A28	USGSbPROJECTIONbPARAMETERSb=
	10	109	109	1X	Blank fill
	11	110	133	D24.15	USGS projection parameter 1: Semi-major axis
	12	134	134	1X	Blank fill
	13	135	158	D24.15	USGS projection parameter 2: Semi-minor axis
	14	159	159	1X	Blank fill
	15	160	160	A1	Carriage return
3	16	161	184	D24.15	USGS projection parameter 3
	17	185	185	1X	Blank fill
	18	186	209	D24.15	USGS projection parameter 4
	19	210	210	1X	Blank fill
	20	211	234	D24.15	USGS projection parameter 5
	21	235	239	5X	Blank fill
	22	240	240	A1	Carriage return
4	23	241	264	D24.15	USGS projection parameter 6
	24	265	265	1X	Blank fill
	25	266	289	D24.15	USGS projection parameter 7
	26	290	290	1X	Blank fill
	27	291	314	D24.15	USGS projection parameter 8
	28	315	319	5X	Blank fill
	29	320	320	A1	Carriage return
5	30	321	344	D24.15	USGS projection parameter 9
	31	345	345	1X	Blank fill
	32	346	369	D24.15	USGS projection parameter 10
	33	370	370	1X	Blank fill
	34	371	394	D24.15	USGS projection parameter 11
	35	395	399	5X	Blank fill
	36	400	400	A1	Carriage return
6	37	401	424	D24.15	USGS projection parameter 12
	38	425	425	1X	Blank fill
	39	426	449	D24.15	USGS projection parameter 13
	40	450	450	1X	Blank fill
	41	451	474	D24.15	USGS projection parameter 14
	42	475	479	5X	Blank fill
	43	480	480	A1	Carriage return
7	44	481	504	D24.15	USGS projection parameter 15
	45	505	505	A1	Blank fill
	46	506	520	A15	USGSbMAPbZONEb=
	47	521	526	I6	Zone number
	48	527	559	33X	Blank fill
	49	560	560	A1	Carriage return
8	50	561	564	A4	ULb=
	51	565	565	1X	Blank fill
	52	566	578	A13	Geodetic longitude of upper-left corner of product; longitude is

Line	Field	Start Byte	End Byte	Format	Description
					expressed as degrees, minutes, seconds; e.g., 5 degrees, 15 minutes, 13.2 seconds west of the prime meridian is expressed as 0051513.2000W
	53	579	579	1X	Blank fill
	54	580	591	A12	Geodetic latitude of upper-left corner of product; latitude is expressed as degrees, minutes, seconds; e.g., 9 degrees, 4 minutes, 24.2334 seconds north of the equator is expressed as 090424.2334N
	55	592	592	1X	Blank fill
	56	593	605	F13.3	Easting of upper-left corner of product in projection units (meters only)
	57	606	606	1X	Blank fill
	58	607	619	F13.3	Northing of upper-left corner of product in projection units (meters only)
	59	620	639	20X	Blank fill
	60	640	640	A1	Carriage return
9	61	641	644	A4	URb=
	62	645	645	1X	Blank fill
	63	646	658	A13	Geodetic longitude of upper-right corner of product
	64	659	659	1X	Blank fill
	65	660	671	A12	Geodetic latitude of upper-right corner of product
	66	672	672	1X	Blank fill
	67	673	685	F13.3	Easting of upper-right corner of product in projection units (meters only)
	68	686	686	1X	Blank fill
	69	687	699	F13.3	Northing of upper-right corner of product in projection units (meters only)
	70	700	719	20X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	724	A4	LRb=
	73	725	725	1X	Blank fill
	74	726	738	A13	Geodetic longitude of lower-right corner of product
	75	739	739	1X	Blank fill
	76	740	751	A12	Geodetic latitude of lower-right corner of product
	77	752	752	1X	Blank fill
	78	753	765	F13.3	Easting of lower-right corner of product in projection units (meters only)
	79	766	766	1X	Blank fill
	80	767	779	F13.3	Northing of lower-right corner of product in projection units (meters only)
	81	780	799	20X	Blank fill
	82	800	800	A1	Carriage return
11	83	801	804	A4	LLb=
	84	805	805	1X	Blank fill
	85	806	818	A13	Geodetic longitude of lower-left corner of product
	86	819	819	1X	Blank fill
	87	820	831	A12	Geodetic latitude of lower-left corner of product
	88	832	832	1X	Blank fill
	89	833	845	F13.3	Easting of lower-left corner of product in projection units (meters only)
	90	846	846	1X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	91	847	859	F13.3	Northing of lower-left corner of product in projection units (meters only)
	92	860	879	20X	Blank fill
	93	880	880	A1	Carriage return
12	94	881	888	A8	CENTERb=
	95	889	889	1X	Blank fill
	96	890	902	A13	Product center geodetic longitude expressed in degrees, minutes, seconds, as above. This is the true center of the input imagery from which the product was made and does not necessarily fall inside the product.
	97	903	903	1X	Blank fill
	98	904	915	A12	Product center geodetic latitude expressed in degrees, minutes, seconds, as above. This is the true center of the input imagery from which the product was made and does not necessarily fall inside the product.
	99	916	916	1X	Blank fill
	100	917	929	F13.3	Product center easting in projection units (meters only)
	101	930	930	1X	Blank fill
	102	931	943	F13.3	Product center northing in projection units (meters only)
	103	944	944	1X	Blank fill
	104	945	949	I5	Product center pixel number measured from the product upper-left corner, rounded to nearest whole pixel
	105	950	950	1X	Blank fill
	106	951	955	I5	Product center line number measured from the product upper-left corner, rounded to nearest whole pixel
	107	956	959	4X	Blank fill
	108	960	960	A1	Carriage return
13	109	961	968	A8	OFFSETb=
	110	969	974	I6	Horizontal offset of the true product from the nominal product center calculated in meters; calculated as an average (may be negative)
	111	975	994	20A	bORIENTATIONbANGLEb=
	112	995	1000	F6.2	Nominal (path-oriented) orientation angle in degrees (may be negative) referenced from north up (map-oriented); north up (map-oriented) orientation angle will always have a value of 0.0
	113	1001	1039	39X	Blank fill
	114	1040	1040	A1	Carriage return
14	115	1041	1061	21A	SUNbELEVATIONbANGLEb=
	116	1062	1065	F4.1	Sun elevation angle in degrees at product center
	117	1066	1085	A20	bSUNbAZIMUTHbANGLEb=
	118	1086	1090	F5.1	Sun azimuth in degrees at product center
	119	1091	1119	29X	Blank fill
	120	1120	1120	A1	Carriage return
15	121	1121	1199	79X	Blank fill
	122	1200	1200	A1	Carriage return
16	123	1201	1279	79X	Blank fill
	124	1280	1280	A1	Carriage return
17	125	1281	1359	79X	Blank fill
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1535	15X	Blank fill
	132	1536	1536	A1	Carriage return

Table 3-3. Geometric Record for Panchromatic Band

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	8	A8	REQbIDb=
	2	9	28	A20	Data producer-defined request number that uniquely identifies each product; USGS products use the NNNYYMMDDSSSS_UUUUUU format, where: NNNYYMMDDSSSS = 13-digit DORRAN order number NNN = Node indicator YY = Year MM = Month DD = Day SSSS = Sequence number for the day UUUUU = 5-digit DORRAN unit number
	3	29	34	A6	bLOCb=
	4	35	51	A17	First scene starting location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	5	52	70	A19	bACQUISITIONbDATEb=
	6	71	78	A8	First scene acquisition date in yyyyymmdd format
	7	79	79	1X	Blank fill
	8	80	80	A1	Carriage return
2	9	81	91	A11	SATELLITEb=
	10	92	101	A10	First scene satellite name: LANDSAT7
	11	102	110	A9	bSENSORb=
	12	111	120	A10	First scene sensor name: ETM+
	13	121	134	A14	bSENSORbMODEb=
	14	135	140	A6	First scene sensor mode: NORMAL
	15	141	153	A13	bLOOKbANGLEb=
	16	154	159	F6.2	First scene off-nadir angle in degrees: 0.0
	17	160	160	A1	Carriage return
3	18	161	183	23X	Blank fill
	19	184	194	A11	bLOCATIONb=
	20	195	211	A17	Last scene ending location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	21	212	230	A19	bACQUISITIONbDATEb=
	22	231	238	A8	Last scene acquisition date in yyyyymmdd format
	23	239	239	1X	Blank fill
	24	240	240	A1	Carriage return
4	25	241	251	A11	SATELLITEb=
	26	252	261	A10	Last scene satellite name: LANDSAT7
	27	262	270	A9	SENSORb=
	28	271	280	A10	Last scene sensor name: ETM+
	29	281	294	A14	bSENSORbMODEb=
	30	295	300	A6	Last scene sensor mode: NORMAL
	31	301	313	A13	bLOOKbANGLEb=

Line	Field	Start Byte	End Byte	Format	Description
	32	314	319	F6.2	Last scene off-nadir angle in degrees: 0.0
	33	320	320	A1	Carriage return
5	34	321	343	23X	Blank fill
	35	344	354	A11	bLOCATIONb=
	36	355	371	A17	N/A
	37	372	390	A19	bACQUISITIONbDATEb=
	38	391	398	A8	N/A
	39	399	399	1X	Blank fill
	40	400	400	A1	Carriage return
6	41	401	411	A11	SATELLITEb=
	42	412	421	A10	N/A
	43	422	430	A9	bSENSORb=
	44	431	440	A10	N/A
	45	441	454	A14	bSENSORbMODEb=
	46	455	460	A6	N/A
	47	461	473	A13	bLOOKbANGLEb=
	48	474	479	F6.2	N/A
	49	480	480	A1	Carriage return
7	50	481	503	23X	Blank fill
	51	504	514	A11	bLOCATIONb=
	52	515	531	A17	N/A
	53	532	550	A19	bACQUISITIONbDATEb=
	54	551	558	A8	N/A
	55	559	559	1X	Blank fill
	56	560	560	A1	Carriage return
8	57	561	571	A11	SATELLITEb=
	58	572	581	A10	N/A
	59	582	590	A9	bSENSORb=
	60	591	600	A10	N/A
	61	601	614	A14	bSENSORbMODEb=
	62	615	620	A6	N/A
	63	621	633	A13	bLOOKbANGLEb=
	64	634	639	F6.2	N/A
	65	640	640	A1	Carriage return
9	66	641	654	A14	PRODUCTbTYPEb=
	67	655	672	A18	Product type: MAPbORIENTEDbbbbbb ORBITbORIENTEDbbbb USERbORIENTEDbbbbbb (NLAPS only) TRUENORTHbORIENTED (NLAPS only)
	68	673	687	A15	bPRODUCTbSIZEb=
	69	688	697	A10	Product size: SUBSCENEbb < 375 scans, < 1 scene FULLbSCENE = 375 scans, = 1 scene MULTISCENE > 375 scans, > 1 scene
	70	698	719	22X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	740	A20	TYPEbOFbPROCESSINGb=
	73	741	751	A11	Type of processing used: SYSTEMATICb SYSTERRAINb PRECISIONbb TERRAINbbbb

Line	Field	Start Byte	End Byte	Format	Description
	74	752	764	A13	bRESAMPLINGb=
	75	765	766	A2	Resampling algorithm used: NN = Nearest Neighbor CC = Cubic Convolution MF = Modulation Transfer Function (LPGS only) BI = Bilinear (NLAPS only) KD = Kaiser Damped (NLAPS only) 16 = 16-Point Sinc (NLAPS only) 8b = 8-Point Sinc (NLAPS only) DW = Damped Window (NLAPS only)
	76	767	799	33X	Blank fill
	77	800	800	A1	Carriage return
11	78	801	819	A19	VOLUMEb#/#bINbSETb=
	79	820	821	I2	Tape volume number in tape set (for multivolume product): N/A
	80	822	822	A1	/
	81	823	824	I2	Number of volumes in tape set (for multivolume product): N/A
	82	825	842	A18	bPIXELbPERbLINEb=
	83	843	847	I5	Number of pixels per product line for VNIR and SWIR bands
	88	876	879	4X	Blank fill
	89	880	880	A1	Carriage return
12	90	881	894	A14	STARTbLINEb#b=
	91	895	899	I5	First product line number on this volume (for multivolume product): N/A
	92	900	917	A18	bBLOCKINGbFACTORb=
	93	918	919	I2	Tape blocking factor: N/A
	94	920	931	A12	bRECbSIZEbb=
	95	932	940	I9	Length of physical file record in bytes per VNIR and SWIR bands
	96	941	953	A13	bPIXELbSIZEb=
	97	954	959	F6.2	Pixel size in meters for VNIR and SWIR bands
	98	960	960	A1	Carriage return
13	99	961	983	A23	OUTPUTbBITSbPERbPIXELb=
	100	984	985	I2	Output bits per pixel: 8
	101	986	1011	A26	bACQUIREDbBITSbPERbPIXELb=
	102	1012	1013	I2	Acquired bits per pixel: 8
	103	1014	1039	26X	Blank fill
	104	1040	1040	A1	Carriage return
14	105	1041	1055	A15	BANDSbPRESENTb=
	106	1056	1087	A32	Image bands present for the VNIR and SWIR bands group:123457 (or subset)
	107	1088	1119	32X	Blank fill
	108	1120	1120	A1	Carriage return
15	109	1121	1130	A10	FILENAMEb=
	110	1131	1159	A29	File name for first band
	111	1160	1169	A10	FILENAMEb=
	112	1170	1198	A29	File name for second band
	113	1199	1199	1X	Blank fill
	114	1200	1200	A1	Carriage return
16	115	1201	1210	A10	FILENAMEb=
	116	1211	1239	A29	File name for third band

Line	Field	Start Byte	End Byte	Format	Description
	117	1240	1249	A10	FILENAMEb=
	117	1250	1278	A29	File name for fourth band
	119	1279	1279	1X	Blank fill
	120	1280	1280	A1	Carriage return
17	121	1281	1290	A10	FILENAMEb=
	122	1291	1319	A29	File name for fifth band
	123	1320	1329	A10	FILENAMEb=
	124	1330	1358	A29	File name for sixth band
	125	1359	1359	1X	Blank fill
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1532	12X	REVbbbbbbbbb
	132	1533	1535	A3	Format version code: L7A
	133	1536	1536	A1	Carriage return

Table 3-4. Administrative Record for VNIR and SWIR Bands

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	50	A50	BIASESbANDbGAINSbINbASCENDINGbBANDbNUMBERbORDERbbb
	2	51	79	29X	Blank fill
	3	80	80	A1	Carriage return
2	4	81	104	D24.15	Bias for first band
	5	105	105	1X	Blank fill
	6	106	129	D24.15	Gain for first band
	7	130	159	30X	Blank fill
	8	160	160	A1	Carriage return
3	9	161	184	D24.15	Bias for second band
	10	185	185	1X	Blank fill
	11	186	209	D24.15	Gain for second band
	12	210	239	30X	Blank fill
	13	240	240	A1	Carriage return
4	14	241	264	D24.15	Bias for third band
	15	265	265	1X	Blank fill
	16	266	289	D24.15	Gain for third band
	17	290	319	30X	Blank fill
	18	320	320	A1	Carriage return
5	19	321	344	D24.15	Bias for fourth band
	20	345	345	1X	Blank fill
	21	346	369	D24.15	Gain for fourth band
	22	370	399	30X	Blank fill
	23	400	400	A1	Carriage return
6	24	401	424	D24.15	Bias for fifth band
	25	425	425	1X	Blank fill
	26	426	449	D24.15	Gain for fifth band
	27	450	479	30X	Blank fill
	28	480	480	A1	Carriage return
7	29	481	504	D24.15	Bias for sixth band
	30	505	505	1X	Blank fill
	31	506	529	D24.15	Gain for sixth band
	32	530	559	30X	Blank fill
	33	560	560	A1	Carriage return
8	34	561	584	D24.15	Bias for seventh band
	35	585	585	1X	Blank fill
	36	586	609	D24.15	Gain for seventh band
	37	610	639	30X	Blank fill
	38	640	640	A1	Carriage return
9	39	641	664	D24.15	Bias for eighth band
	40	665	665	1X	Blank fill
	41	666	689	D24.15	Gain for eighth band
	42	690	719	30X	Blank fill
	43	720	720	A1	Carriage return
10	44	721	799	79X	Blank fill
	45	800	800	A1	Carriage return
11	46	801	879	79X	Blank fill
	47	880	880	A1	Carriage return
12	48	881	959	79X	Blank fill
	49	960	960	A1	Carriage return
13	50	961	1039	79X	Blank fill
	51	1040	1040	A1	Carriage return
14	52	1041	1119	79X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	53	1120	1120	A1	Carriage return
15	54	1121	1199	79X	Blank fill
	55	1200	1200	A1	Carriage return
16	56	1201	1279	79X	Blank fill
	57	1280	1280	A1	Carriage return
17	58	1281	1359	79X	Blank fill
	59	1360	1360	A1	Carriage return
18	60	1361	1439	79X	Blank fill
	61	1440	1440	A1	Carriage return
19	62	1441	1519	79X	Blank fill
	63	1520	1520	A1	Carriage return
20	64	1521	1535	15X	Blank fill
	65	1536	1536	A1	Carriage return

Table 3-5. Radiometric Record for VNIR and SWIR Bands

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	14	A14	GEOMETRICbDATA
	2	15	31	A17	bMAPbPROJECTIONb=
	3	32	35	A4	Map projection name (see Appendix A for a list of mnemonics)
	4	36	47	A12	bELLIPSOIDb=
	5	48	65	A18	Earth ellipsoid used
	6	66	73	A8	bDATUMB=
	7	74	79	A6	Datum name
	8	80	80	A1	Carriage return
2	9	81	108	A28	USGSbPROJECTIONbPARAMETERSb=
	10	109	109	1X	Blank fill
	11	110	133	D24.15	USGS projection parameter 1: Semi-major axis
	12	134	134	1X	Blank fill
	13	135	158	D24.15	USGS projection parameter 2: Semi-minor axis
	14	159	159	1X	Blank fill
	15	160	160	A1	Carriage return
3	16	161	184	D24.15	USGS projection parameter 3
	17	185	185	1X	Blank fill
	18	186	209	D24.15	USGS projection parameter 4
	19	210	210	1X	Blank fill
	20	211	234	D24.15	USGS projection parameter 5
	21	235	239	5X	Blank fill
	22	240	240	A1	Carriage return
4	23	241	264	D24.15	USGS projection parameter 6
	24	265	265	1X	Blank fill
	25	266	289	D24.15	USGS projection parameter 7
	26	290	290	1X	Blank fill
	27	291	314	D24.15	USGS projection parameter 8
	28	315	319	5X	Blank fill
	29	320	320	A1	Carriage return
5	30	321	344	D24.15	USGS projection parameter 9
	31	345	345	1X	Blank fill
	32	346	369	D24.15	USGS projection parameter 10
	33	370	370	1X	Blank fill
	34	371	394	D24.15	USGS projection parameter 11
	35	395	399	5X	Blank fill
	36	400	400	A1	Carriage return
6	37	401	424	D24.15	USGS projection parameter 12
	38	425	425	1X	Blank fill
	39	426	449	D24.15	USGS projection parameter 13
	40	450	450	1X	Blank fill
	41	451	474	D24.15	USGS projection parameter 14
	42	475	479	5X	Blank fill
	43	480	480	A1	Carriage return
7	44	481	504	D24.15	USGS projection parameter 15
	45	505	505	A1	Blank fill
	46	506	520	A15	USGSbMAPbZONEb=
	47	521	526	I6	Zone number
	48	527	559	33X	Blank fill
	49	560	560	A1	Carriage return
8	50	561	564	A4	ULb=
	51	565	565	1X	Blank fill
	52	566	578	A13	Geodetic longitude of upper-left corner, expressed

Line	Field	Start Byte	End Byte	Format	Description
					as degrees, minutes, seconds; e.g., 5 degrees, 15 minutes, 13.2 seconds west of the prime meridian is expressed as 0051513.2000W
	53	579	579	1X	Blank fill
	54	580	591	A12	Geodetic latitude of upper-left corner, expressed as degrees, minutes, seconds; e.g., 9 degrees, 4 minutes, 24.2334 seconds north of the equator is expressed as 090424.2334N
	55	592	592	1X	Blank fill
	56	593	605	F13.3	Easting of upper-left corner of product in projection units (meters only)
	57	606	606	1X	Blank fill
	58	607	619	F13.3	Northing of upper-left corner of product in projection units (meters only)
	59	620	639	20X	Blank fill
	60	640	640	A1	Carriage return
9	61	641	644	A4	URb=
	62	645	645	1X	Blank fill
	63	646	658	A13	Geodetic longitude of upper-right corner of product
	64	659	659	1X	Blank fill
	65	660	671	A12	Geodetic latitude of upper-right corner of product
	66	672	672	1X	Blank fill
	67	673	685	F13.3	Easting of upper-right corner of product in projection units (meters only)
	68	686	686	1X	Blank fill
	69	687	699	F13.3	Northing of upper-right corner of product in projection units (meters only)
	70	700	719	20X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	724	A4	LRb=
	73	725	725	1X	Blank fill
	74	726	738	A13	Geodetic longitude of lower-right corner of product
	75	739	739	1X	Blank fill
	76	740	751	A12	Geodetic latitude of lower-right corner of product
	77	752	752	1X	Blank fill
	78	753	765	F13.3	Easting of lower-right corner of product in projection units (meters only)
	79	766	766	1X	Blank fill
	80	767	779	F13.3	Northing of lower-right corner of product in projection units (meters only)
	81	780	799	20X	Blank fill
	82	800	800	A1	Carriage return
11	83	801	804	A4	LLb=
	84	805	805	1X	Blank fill
	85	806	818	A13	Geodetic longitude of lower-left corner of product
	86	819	819	1X	Blank fill
	87	820	831	A12	Geodetic latitude of lower-left corner of product
	88	832	832	1X	Blank fill
	89	833	845	F13.3	Easting of lower-left corner of product in projection units (meters only)
	90	846	846	1X	Blank fill
	91	847	859	F13.3	Northing of lower-left corner of product in projection units (meters only)

Line	Field	Start Byte	End Byte	Format	Description
	92	860	879	20X	Blank fill
	93	880	880	A1	Carriage return
12	94	881	888	A8	CENTERb=
	95	889	889	1X	Blank fill
	96	890	902	A13	Product center geodetic longitude expressed in degrees, minutes, seconds; this is the true center of the input imagery from which the product was made, and does not necessarily fall inside the product
	97	903	903	1X	Blank fill
	98	904	915	A12	Product center geodetic latitude expressed in degrees, minutes, seconds; this is the true center of the input imagery from which the product was made, and does not necessarily fall inside the product
	99	916	916	1X	Blank fill
	100	917	929	F13.3	Product center easting in projection units (meters only)
	101	930	930	1X	Blank fill
	102	931	943	F13.3	Product center northing in projection units (meters only)
	103	944	944	1X	Blank fill
	104	945	949	I5	Product center pixel number measured from the product's upper-left corner, rounded to nearest whole pixel
	105	950	950	1X	Blank fill
	106	951	955	I5	Product center line number measured from the product's upper-left corner, rounded to nearest whole pixel
	107	956	959	4X	Blank fill
	108	960	960	A1	Carriage return
13	109	961	968	A8	OFFSETb=
	110	969	974	I6	Horizontal offset of the true product from the nominal product center, calculated in meters; calculated as an average (may be negative)
	111	975	994	20A	bORIENTATIONbANGLEb=
	112	995	1000	F6.2	Nominal (path-oriented) orientation angle in degrees (may be negative) referenced from north up (map-oriented); north up (map-oriented) orientation angle always has a value of 0.0
	113	1001	1039	39X	Blank fill
	114	1040	1040	A1	Carriage return
14	115	1041	1061	21A	SUNbELEVATIONbANGLEb=
	116	1062	1065	F4.1	Sun elevation angle in degrees at product center
	117	1066	1085	A20	bSUNbAZIMUTHbANGLEb=
	118	1086	1090	F5.1	Sun azimuth in degrees at product center
	119	1091	1119	29X	Blank fill
	120	1120	1120	A1	Carriage return
15	121	1121	1199	79X	Blank fill
	122	1200	1200	A1	Carriage return
16	123	1201	1279	79X	Blank fill
	124	1280	1280	A1	Carriage return
17	125	1281	1359	79X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1535	15X	Blank fill
	132	1536	1536	A1	Carriage return

Table 3-6. Geometric Record for VNIR and SWIR Bands

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	8	A8	REQbIDb=
	2	9	28	A20	Data producer-defined request number that uniquely identifies each product; USGS products use the NNNYYMMDDSSSS_UUUUUb format, where: NNNYYMMDDSSSS = 13-digit DORRAN order number NNN = Node indicator YY = Year MM = Month DD = Day SSSS = Sequence number for the day UUUUU = 5-digit DORRAN unit number
	3	29	34	A6	bLOCb=
	4	35	51	A17	First scene starting location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	5	52	70	A19	bACQUISITIONbDATEb=
	6	71	78	A8	First scene acquisition date in yyymmdd format
	7	79	79	1X	Blank fill
	8	80	80	A1	Carriage return
2	9	81	91	A11	SATELLITEb=
	10	92	101	A10	First scene satellite name: LANDSAT 7
	11	102	110	A9	bSENSORb=
	12	111	120	A10	First scene sensor name: ETM+
	13	121	134	A14	bSENSORbMODEb=
	14	135	140	A6	First scene sensor mode: NORMAL
	15	141	153	A13	bLOOKbANGLEb=
	16	154	159	F6.2	First scene off-nadir angle in degrees: 0.0
	17	160	160	A1	Carriage return
3	18	161	183	23X	Blank fill
	19	184	194	A11	bLOCATIONb=
	20	195	211	A17	Last scene ending location in ppp/rrrffssbbbbb format, where: ppp = path / = / rrr = row ff = fraction ss = subscene
	21	212	230	A19	bACQUISITIONbDATEb=
	22	231	238	A8	Last scene acquisition date in yyymmdd format
	23	239	239	1X	Blank fill
	24	240	240	A1	Carriage return
4	25	241	251	A11	SATELLITEb=
	26	252	261	A10	Last scene satellite name: LANDSAT 7
	27	262	270	A9	bSENSORb=
	28	271	280	A10	Last scene sensor name: ETM+
	29	281	294	A14	bSENSORbMODEb=
	30	295	300	A6	Last scene sensor mode: NORMAL
	31	301	313	A13	bLOOKbANGLEb=

Line	Field	Start Byte	End Byte	Format	Description
	32	314	319	F6.2	Last scene off-nadir angle in degrees: 0.0
	33	320	320	A1	Carriage return
5	34	321	343	23X	Blank fill
	35	344	354	A11	bLOCATIONb=
	36	355	371	A17	N/A
	37	372	390	A19	bACQUISITIONbDATEb=
	38	391	398	A8	N/A
	39	399	399	1X	Blank fill
	40	400	400	A1	Carriage return
6	41	401	411	A11	SATELLITEb=
	42	412	421	A10	N/A
	43	422	430	A9	bSENSORb=
	44	431	440	A10	N/A
	45	441	454	A14	bSENSORbMODEb=
	46	455	460	A6	N/A
	47	461	473	A13	bLOOKbANGLEb=
	48	474	479	F6.2	N/A
	49	480	480	A1	Carriage return
7	50	481	503	23X	Blank fill
	51	504	514	A11	bLOCATIONb=
	52	515	531	A17	N/A
	53	532	550	A19	bACQUISITIONbDATEb=
	54	551	558	A8	N/A
	55	559	559	1X	Blank fill
	56	560	560	A1	Carriage return
8	57	561	571	A11	SATELLITEb=
	58	572	581	A10	N/A
	59	582	590	A9	bSENSORb=
	60	591	600	A10	N/A
	61	601	614	A14	bSENSORbMODEb=
	62	615	620	A6	N/A
	63	621	633	A13	bLOOKbANGLEb=
	64	634	639	F6.2	N/A
	65	640	640	A1	Carriage return
9	66	641	654	A14	PRODUCTbTYPEb=
	67	655	672	A18	Product type: MAPbORIENTEDbbbbbb ORBITbORIENTEDbbbb USERbORIENTEDbbbbbb (NLAPS only) TRUENORTHbORIENTED (NLAPS only)
	68	673	687	A15	PRODUCTbSIZEb=
	69	688	697	A10	Product size: SUBSCENEbb < 375 scans, < 1 scene FULLbSCENE = 375 scans, = 1 scene MULTISCENE > 375 scans, > 1 scene
	70	698	719	22X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	740	A20	TYPEbOFbPROCESSINGb=
	73	741	751	A11	Type of processing used: SYSTEMATICb SYSTERRAINb PRECISIONbb TERRAINbbbb

Line	Field	Start Byte	End Byte	Format	Description
	74	752	764	A13	bRESAMPLINGb=
	75	765	766	A2	Resampling algorithm used: NN = Nearest Neighbor CC = Cubic Convolution MF = Modulation Transfer Function (LPGS only) BI = Bilinear (NLAPS only) KD = Kaiser Damped (NLAPS only) 16 = 16-Point Sinc (NLAPS only) 8b = 8-Point Sinc (NLAPS only) DW = Damped Window (NLAPS only)
	76	767	799	33X	Blank fill
	77	800	800	A1	Carriage return
11	78	801	819	A19	VOLUMEb#/#bINbSETb=
	79	820	821	I2	Tape volume number in tape set (for multivolume product): N/A
	80	822	822	A1	/
	81	823	824	I2	Number of volumes in tape set (for multivolume product): N/A
	82	825	842	A18	bPIXELsbPERbLINEb=
	83	843	847	I5	Number of pixels per product line for thermal band
	84	848	864	A17	bLINESbPERbBANDb=
	85	865	869	I5	Number of lines per thermal band
	86	870	870	A1	/
	87	871	875	I5	Number of lines in output product
	88	876	879	4X	Blank fill
	89	880	880	A1	Carriage return
12	90	881	894	A14	STARTbLINEb#b=
	91	895	899	I5	First product line number on this volume (for multivolume product): N/A
	92	900	917	A18	bBLOCKINGbFACTORb=
	93	918	919	I2	Tape blocking factor: N/A
	94	920	931	A12	bRECBbSIZEbb=
	95	932	940	I9	Length of physical file record in bytes per thermal band
	96	941	953	A13	bPIXELbSIZEb=
	97	954	959	F6.2	Pixel size in meters for thermal band
	98	960	960	A1	Carriage return
13	99	961	983	A23	OUTPUTbBITSBPERbPIXELb=
	100	984	985	I2	Output bits per pixel: 8
	101	986	1011	A26	bACQUIREDbBITSBPERbPIXELb=
	102	1012	1013	I2	Acquired bits per pixel: 8
	103	1014	1039	26X	Blank fill
	104	1040	1040	A1	Carriage return
14	105	1041	1055	A15	BANDSbPRESENTb=
	106	1056	1087	A32	Image bands present for the thermal band group: LH (or subset)
	107	1088	1119	32X	Blank fill
	108	1120	1120	A1	Carriage return
15	109	1121	1130	A10	FILENAMEb=
	110	1131	1159	A29	File name for first band
	111	1160	1169	A10	FILENAMEb=
	112	1170	1198	A29	File name for second band

Line	Field	Start Byte	End Byte	Format	Description
	113	1199	1199	1X	Blank fill
	114	1200	1200	A1	Carriage return
16	115	1201	1210	A10	FILENAMEb=
	116	1211	1239	A29	File name for third band
	117	1240	1249	A10	FILENAMEb=
	117	1250	1278	A29	File name for fourth band
	119	1279	1279	1X	Blank fill
	120	1280	1280	A1	Carriage return
17	121	1281	1290	A10	FILENAMEb=
	122	1291	1319	A29	File name for fifth band
	123	1320	1329	A10	FILENAMEb=
	124	1330	1358	A29	File name for sixth band
	125	1359	1359	1X	Blank fill
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1532	12X	REVbbbbbbbbb
	132	1533	1535	A3	Format version code: L7A
	133	1536	1536	A1	Carriage return

Table 3-7. Administrative Record for Thermal Bands

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	50	A50	BIASESbANDbGAINSbINbASCENDINGbBANDbNUMBERbORDERbbb
	2	51	79	29X	Blank fill
	3	80	80	A1	Carriage return
2	4	81	104	D24.15	Bias for first band
	5	105	105	1X	Blank fill
	6	106	129	D24.15	Gain for first band
	7	130	159	30X	Blank fill
	8	160	160	A1	Carriage return
3	9	161	184	D24.15	Bias for second band
	10	185	185	1X	Blank fill
	11	186	209	D24.15	Gain for second band
	12	210	239	30X	Blank fill
	13	240	240	A1	Carriage return
4	14	241	264	D24.15	Bias for third band
	15	265	265	1X	Blank fill
	16	266	289	D24.15	Gain for third band
	17	290	319	30X	Blank fill
	18	320	320	A1	Carriage return
5	19	321	344	D24.15	Bias for fourth band
	20	345	345	1X	Blank fill
	21	346	369	D24.15	Gain for fourth band
	22	370	399	30X	Blank fill
	23	400	400	A1	Carriage return
6	24	401	424	D24.15	Bias for fifth band
	25	425	425	1X	Blank fill
	26	426	449	D24.15	Gain for fifth band
	27	450	479	30X	Blank fill
	28	480	480	A1	Carriage return
7	29	481	504	D24.15	Bias for sixth band
	30	505	505	1X	Blank fill
	31	506	529	D24.15	Gain for sixth band
	32	530	559	30X	Blank fill
	33	560	560	A1	Carriage return
8	34	561	584	D24.15	Bias for seventh band
	35	585	585	1X	Blank fill
	36	586	609	D24.15	Gain for seventh band
	37	610	639	30X	Blank fill
	38	640	640	A1	Carriage return
9	39	641	664	D24.15	Bias for eighth band
	40	665	665	1X	Blank fill
	41	666	689	D24.15	Gain for eighth band
	42	690	719	30X	Blank fill
	43	720	720	A1	Carriage return
10	44	721	799	79X	Blank fill
	45	800	800	A1	Carriage return
11	46	801	879	79X	Blank fill
	47	880	880	A1	Carriage return
12	48	881	959	79X	Blank fill
	49	960	960	A1	Carriage return
13	50	961	1039	79X	Blank fill
	51	1040	1040	A1	Carriage return

Line	Field	Start Byte	End Byte	Format	Description
14	52	1041	1119	79X	Blank fill
	53	1120	1120	A1	Carriage return
15	54	1121	1199	79X	Blank fill
	55	1200	1200	A1	Carriage return
16	56	1201	1279	79X	Blank fill
	57	1280	1280	A1	Carriage return
17	58	1281	1359	79X	Blank fill
	59	1360	1360	A1	Carriage return
18	60	1361	1439	79X	Blank fill
	61	1440	1440	A1	Carriage return
19	62	1441	1519	79X	Blank fill
	63	1520	1520	A1	Carriage return
20	64	1521	1535	15X	Blank fill
	65	1536	1536	A1	Carriage return

Table 3-8. Radiometric Record for Thermal Bands

Line	Field	Start Byte	End Byte	Format	Description
1	1	1	14	A14	GEOMETRICbDATA
	2	15	31	A17	bMAPbPROJECTIONb=
	3	32	35	A4	Map projection name (see Appendix A for list of mnemonics)
	4	36	47	A12	bELLIPSOIDb=
	5	48	65	A18	Earth ellipsoid used
	6	66	73	A8	bDATUMB=
	7	74	79	A6	Datum name
	8	80	80	A1	Carriage return
2	9	81	108	A28	USGSbPROJECTIONbPARAMETERSb=
	10	109	109	1X	Blank fill
	11	110	133	D24.15	USGS projection parameter 1: Semi-major axis
	12	134	134	1X	Blank fill
	13	135	158	D24.15	USGS projection parameter 2: Semi-minor axis
	14	159	159	1X	Blank fill
	15	160	160	A1	Carriage return
3	16	161	184	D24.15	USGS projection parameter 3
	17	185	185	1X	Blank fill
	18	186	209	D24.15	USGS projection parameter 4
	19	210	210	1X	Blank fill
	20	211	234	D24.15	USGS projection parameter 5
	21	235	239	5X	Blank fill
	22	240	240	A1	Carriage return
4	23	241	264	D24.15	USGS projection parameter 6
	24	265	265	1X	Blank fill
	25	266	289	D24.15	USGS projection parameter 7
	26	290	290	1X	Blank fill
	27	291	314	D24.15	USGS projection parameter 8
	28	315	319	5X	Blank fill
	29	320	320	A1	Carriage return
5	30	321	344	D24.15	USGS projection parameter 9
	31	345	345	1X	Blank fill
	32	346	369	D24.15	USGS projection parameter 10
	33	370	370	1X	Blank fill
	34	371	394	D24.15	USGS projection parameter 11
	35	395	399	5X	Blank fill
	36	400	400	A1	Carriage return
6	37	401	424	D24.15	USGS projection parameter 12
	38	425	425	1X	Blank fill
	39	426	449	D24.15	USGS projection parameter 13
	40	450	450	1X	Blank fill
	41	451	474	D24.15	USGS projection parameter 14
	42	475	479	5X	Blank fill
	43	480	480	A1	Carriage return
7	44	481	504	D24.15	USGS projection parameter 15
	45	505	505	A1	Blank fill
	46	506	520	A15	USGSbMAPbZONEb=
	47	521	526	I6	Zone number
	48	527	559	33X	Blank fill
	49	560	560	A1	Carriage return
8	50	561	564	A4	ULb=
	51	565	565	1X	Blank fill
	52	566	578	A13	Geodetic longitude of upper-left corner expressed

Line	Field	Start Byte	End Byte	Format	Description
					as degrees, minutes, seconds; e.g., 5 degrees, 15 minutes, 13.2 seconds west of the prime meridian is expressed as 0051513.2000W
	53	579	579	1X	Blank fill
	54	580	591	A12	Geodetic latitude of upper-left corner expressed as degrees, minutes, seconds; e.g., 9 degrees, 4 minutes, 24.2334 seconds north of the equator is expressed as 090424.2334N
	55	592	592	1X	Blank fill
	56	593	605	F13.3	Easting of upper-left corner of product in projection units (meters only)
	57	606	606	1X	Blank fill
	58	607	619	F13.3	Northing of upper-left corner of product in projection units (meters only)
	59	620	639	20X	Blank fill
	60	640	640	A1	Carriage return
9	61	641	644	A4	URb=
	62	645	645	1X	Blank fill
	63	646	658	A13	Geodetic longitude of upper-right corner of product
	64	659	659	1X	Blank fill
	65	660	671	A12	Geodetic latitude of upper-right corner of product
	66	672	672	1X	Blank fill
	67	673	685	F13.3	Easting of upper-right corner of product in projection units (meters only)
	68	686	686	1X	Blank fill
	69	687	699	F13.3	Northing of upper-right corner of product in projection units (meters only)
	70	700	719	20X	Blank fill
	71	720	720	A1	Carriage return
10	72	721	724	A4	LRb=
	73	725	725	1X	Blank fill
	74	726	738	A13	Geodetic longitude of lower-right corner of product
	75	739	739	1X	Blank fill
	76	740	751	A12	Geodetic latitude of lower-right corner of product
	77	752	752	1X	Blank fill
	78	753	765	F13.3	Easting of lower-right corner of product in projection units (meters only)
	79	766	766	1X	Blank fill
	80	767	779	F13.3	Northing of lower-right corner of product in projection units (meters only)
	81	780	799	20X	Blank fill
	82	800	800	A1	Carriage return
11	83	801	804	A4	LLb=
	84	805	805	1X	Blank fill
	85	806	818	A13	Geodetic longitude of lower-left corner of product
	86	819	819	1X	Blank fill
	87	820	831	A12	Geodetic latitude of lower-left corner of product
	88	832	832	1X	Blank fill
	89	833	845	F13.3	Easting of lower-left corner of product in projection units (meters only)
	90	846	846	1X	Blank fill
	91	847	859	F13.3	Northing of lower-left corner of product in projection units (meters only)

Line	Field	Start Byte	End Byte	Format	Description
	92	860	879	20X	Blank fill
	93	880	880	A1	Carriage return
12	94	881	888	A8	CENTERb=
	95	889	889	1X	Blank fill
	96	890	902	A13	Product center geodetic longitude expressed in degrees, minutes, seconds; this is the true center of the input imagery from which the product was made and does not necessarily fall inside the product
	97	903	903	1X	Blank fill
	98	904	915	A12	Product center geodetic latitude expressed in degrees, minutes, seconds; this is the true center of the input imagery from which the product was made and does not necessarily fall inside the product
	99	916	916	1X	Blank fill
	100	917	929	F13.3	Product center easting in projection units (meters only)
	101	930	930	1X	Blank fill
	102	931	943	F13.3	Product center northing in projection units (meters only)
	103	944	944	1X	Blank fill
	104	945	949	I5	Product center pixel number measured from the product upper-left corner, rounded to nearest whole pixel
	105	950	950	1X	Blank fill
	106	951	955	I5	Product center line number measured from the product upper-left corner, rounded to nearest whole pixel
	107	956	959	4X	Blank fill
	108	960	960	A1	Carriage return
13	109	961	968	A8	OFFSETb=
	110	969	974	I6	Horizontal offset of the true product from the nominal product center calculated in meters; calculated as an average (may be negative)
	111	975	994	20A	bORIENTATIONbANGLEb=
	112	995	1000	F6.2	Nominal (path-oriented) orientation angle in degrees (may be negative) referenced from north up (map-oriented); north up (map-oriented) orientation angle always has a value of 0.0
	113	1001	1039	39X	Blank fill
	114	1040	1040	A1	Carriage return
14	115	1041	1061	21A	SUNbELEVATIONbANGLEb=
	116	1062	1065	F4.1	Sun elevation angle in degrees at product center
	117	1066	1085	A20	bSUNbAZIMUTHbANGLEb=
	118	1086	1090	F5.1	Sun azimuth in degrees at product center
	119	1091	1119	29X	Blank fill
	120	1120	1120	A1	Carriage return
15	121	1121	1199	79X	Blank fill
	122	1200	1200	A1	Carriage return
16	123	1201	1279	79X	Blank fill
	124	1280	1280	A1	Carriage return
17	125	1281	1359	79X	Blank fill
	126	1360	1360	A1	Carriage return
18	127	1361	1439	79X	Blank fill

Line	Field	Start Byte	End Byte	Format	Description
	128	1440	1440	A1	Carriage return
19	129	1441	1519	79X	Blank fill
	130	1520	1520	A1	Carriage return
20	131	1521	1535	15X	Blank fill
	132	1536	1536	A1	Carriage return

Table 3-9. Geometric Record for Thermal Bands

3.1.3 Level 1 Metadata File

Please see Section 3.3.2 for L1 Metadata File details.

3.1.4 Gap Mask

The gap masks are 8-bit images having dimensions identical to the corresponding image band files to simplify data access and viewing. The gap masks use a code to identify fill pixels. The gap mask uses code 0 to represent no data and codes 1-6 to identify how pixels are filled. Table 3-10 lists the data to which they correspond.

Value	Gap-Filled Products	Segmentation Gap-Filled Product
0	No data	No data
1	Primary scene	Primary scene
2	Fill scene 1	Pixel filled with segment level 10
3	Fill scene 2	Pixel filled with segment level 15
4	Fill scene 3	Pixel filled with segment level 20
5	Fill scene 4	Pixel filled using nearest neighbor
6	Fill scene 5	Not used

Table 3-10. Gap Mask Codes

3.2 GeoTIFF File Formats

3.2.1 Level 1 Image File

The description of an image in GeoTIFF requires tags and keys as described in Applicable Document 5 (See References). These tags and keys are included in the L1 Image Files and are automatically detected and read by TIFF readers. They are described in the following subsections.

Each Earth image band in the requested product is contained in a separate file. The data are laid out in a scan line sequential format in descending detector order (i.e., detector 16 is followed by detector 15 and so forth for the 30-m bands). The L1R image is radiometrically corrected, but is not geometrically resampled. The L1T image is radiometric, geometric, and precision corrected and uses a DEM to correct parallax error due to local topographic relief. The L1G image is radiometrically corrected and resampled for geometric correction and registration to geographic map projections.

3.2.1.1 GeoTIFF Tags

TIFF tags convey metadata information about the image. The tags describe the image with information the TIFF reader needs to control the appearance of the image on the user's screen. The TIFF tags are in the same file as the TIFF image.

A complete description of the raster data requires georeferencing of the data, which is accomplished by using tags. L7 L1 production systems use the transformation raster and model space tie points and scaling parameters. ModelTiepointTag and ModelPixelScaleTag are used for this purpose.

3.2.1.1.1 ModelTiepointTag

Tag = 33922

Type = DOUBLE

N = 6*K, K = number of tiepoints

Alias: GeoreferenceTag

Owner: Intergraph

This tag stores the raster-to-model tiepoint pairs in the order

ModelTiepointTag = (... , I, J, K, X, Y, Z...)

where (I, J, K) is the point at location (I, J) in raster space with pixel-value K, and (X, Y, Z) is a vector in model space.

The raster image is georeferenced by specifying its location, size, and orientation in the model coordinate space. Because the relationship between the raster space and the model space is often an exact, affine transformation, the relationship can be defined using one set of tiepoints and the ModelPixelScaleTag, which gives the vertical and horizontal raster grid cell size.

3.2.1.1.2 ModelPixelScaleTag

Tag = 33550

Type = DOUBLE

N = 3

Owner: SoftDesk

This tag is used to specify the size of raster pixel spacing in the model space units when the raster space can be embedded in the model space coordinate system without rotation and consists of the following three values:

ModelPixelScaleTag = (ScaleX, ScaleY, ScaleZ)

where ScaleX and ScaleY give the horizontal and vertical spacing of raster pixels, and ScaleZ is used to map the pixel value of a digital elevation model into the correct Z-

scale. ScaleZ is not used for L1G data because it is only systematically corrected and not corrected for elevation.

A single tiepoint in the ModelTiepointTag, together with the ModelPixelScaleTag, completely determines the relationship between raster and model space.

3.2.1.2 GeoTIFF Keys

In addition to tags, the description of a projection in GeoTIFF requires using keys. Table 3-11 lists the keys that are necessary to define the projections supported by the L1 production systems and their possible values.

Valid Keys	Possible Values	Meaning
Transverse Mercator (TM)		
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
GTCitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeographicTypeGeoKey	4326	GCS_WGS_84
GeogLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 - 32760	European Petroleum Survey Group (EPSG) Projection System Codes (see Applicable Document 7 for values)
	32767	User defined
ProjectionGeoKey	10000 - 19999	EPSG/Petrotechnical Open Software Corporation (POSC) Projection Codes (see Applicable Document 7 for values)
	32767	User defined
ProjNatOriginLatGeoKey		Value in units of GeogAngularUnits
ProjScaleAtNatOriginGeoKey		Value entered as a ratio
ProjCenterLongGeoKey		Value entered in units of GeogAngularUnits
ProjLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
ProjFalseNorthingGeoKey		Value entered in units of ProjLinearUnits
ProjFalseEastingGeoKey		Value entered in units of ProjLinearUnits
Universal Transverse Mercator (UTM)		
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
GTCitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeogLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 - 32760	EPSG Projection System Codes (see Applicable Document 7 for values)
	32767	User defined
Oblique Mercator, Type B (OMB)		
ProjCoordTransGeoKey	3	CT_ObliqueMercator
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
GTCitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeographicTypeGeoKey	4326	GCS_WGS_84
GeogLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
GeogAzimuthUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 - 32760	EPSG Projection System Codes (see Applicable Document 7 for values)
	32767	User defined

Valid Keys	Possible Values	Meaning
ProjectionGeoKey	10000 - 19999	EPSG/POSC Projection Codes (see Applicable Document 7 for values)
	32767	User defined
ProjLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
ProjAzimuthAngleGeoKey		Value in units of GeogAngularUnits
ProjScaleAtNatOriginGeoKey		Value entered as a ratio
ProjCenterLatGeoKey		Value in units of GeogAngularUnits
ProjCenterLongGeoKey		Value in units of GeogAngularUnits
ProjFalseNorthingGeoKey		Value entered in units of ProjLinearUnits
ProjFalseEastingGeoKey		Value entered in units of ProjLinearUnits
Lambert Conformal Conic (LCC)		
ProjCoordTransGeoKey	8	CT_LambertConfConic_2SP
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
GT_CitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeographicTypeGeoKey	4326	GCS_WGS_84
GeogLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 -32760	EPSG Projection System Codes (see Applicable Document 7 for values)
	32767	User defined
ProjectionGeoKey	10000 - 19999	EPSG/POSC Projection Codes (see Applicable Document 7 for values)
	32767	User defined
ProjLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
ProjStdParallel1GeoKey		Value in units of GeogAngularUnits
ProjStdParallel2GeoKey		Value in units of GeogAngularUnits
ProjFalseOriginLongGeoKey		Value in units of GeogAngularUnits (default to 0)
ProjFalseOriginLatGeoKey		Value in units of GeogAngularUnits (default to 0)
ProjNatOriginLatGeoKey		Value in units of GeogAngularUnits
ProjNatOriginLongGeoKey		Value in units of GeogAngularUnits (IAS/LPGS)
ProjCenterLongGeoKey		Value in units of GeogAngularUnits (NLAPS)
ProjFalseNorthingGeoKey		Value entered in units of ProjLinearUnits
ProjFalseEastingGeoKey		Value entered in units of ProjLinearUnits
Polar Stereographic (PS)		
ProjCoordTransGeoKey	15	CT_PolarStereographic
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
GTCitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeographicTypeGeoKey	4326	GCS_WGS_84
GeogLinearUnitsGeoKey	9001	Linear_Meter

Valid Keys	Possible Values	Meaning
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 - 32760	EPSG Projection System Codes (see Applicable Document 7 for values)
	32767	User defined
ProjectionGeoKey	10000 - 19999	EPSG/POSC Projection Codes (see Applicable Document 7 for values)
	32767	User defined
ProjLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
ProjStraightVertPoleLongGeoKey		Value in units of GeogAngularUnits
ProjNatOriginLatGeoKey		Value in units of GeogAngularUnits
ProjFalseNorthingGeoKey		Value entered in units of ProjLinearUnits
ProjFalseEastingGeoKey		Value entered in units of ProjLinearUnits
Polyconic (PC)		
ProjCoordTransGeoKey	22	CT_Polyconic
GTModelTypeGeoKey	1	ModelTypeProjected (Projection Coordinate System)
GTRasterTypeGeoKey	1	RasterPixellsArea
	2	RasterPixellsPoint
UTCitationGeoKey	(ASCII, 17)	ASCII reference to public documentation
GeographicTypeGeoKey	4326	GCS_WGS_84
GeogLinearUnitsGeoKey	9001	Linear_Meter
	9002	Linear_Foot
GeogAngularUnitsGeoKey	9102	Angular_Degree
ProjectedCSTypeGeoKey	20000 - 32760	EPSG Projection System Codes (see Applicable Document 7 for values)
	32767	User defined
ProjectionGeoKey	10000 - 19999	EPSG/POSC Projection Codes (see Applicable Document 7 for values)
	32767	User defined
ProjCenterLatGeoKey		Value in units of GeogAngularUnits
ProjCenterLongGeoKey		Value in units of GeogAngularUnits
ProjFalseNorthingGeoKey		Value entered in units of ProjLinearUnits
ProjFalseEastingGeoKey		Value entered in units of ProjLinearUnits
ProjLinearUnitsGeokey	9001	Linear_Meter
	9002	Linear_Foot

Table 3-11. GeoTIFF Keys

3.2.2 Level 1 Metadata File

Please see Section 3.3.2 for L1 Metadata File details.

3.2.3 Gap Mask

Please see Section 3.1.4 for Gap Mask details.

3.3 HDF File Formats

3.3.1 Level 1 Image File

Each Earth image band in the requested product is contained in a separate file. The data are laid out in a scan line sequential format in descending detector order (i.e., detector 16 is followed by detector 15 and so forth for the 30-m bands). The L1R image is radiometrically corrected, but is not geometrically resampled. The L1T image is radiometric, geometric, and precision corrected and uses a DEM to correct parallax error due to local topographic relief. The L1G image is radiometrically corrected and resampled for geometric correction and registration to geographic map projections.

3.3.1.1 HDF Directory File

The directory file contains all of the pointers, file size information, and data objects required to open and process the L1 product using the HDF library and interface routines.

3.3.1.2 Vgroup Definitions

The Vgroup structure was designed to associate related HDF data objects. Any HDF data object (e.g., Vdata, Scientific Data Sets [SDSs], and attributes) can be included in an HDF Vgroup definition. Vgroup employ Vgroup names and Vgroup classes for characterizing a collection of data objects and for searching activities. Three classes are recognized for the L1 HDF product: image data, correction data, and metadata.

The HDF Vgroup interface consists of routines for accessing and getting information about the L1 product Vgroup. This information is stored in the HDF data directory.

Table 3-12 presents the Vgroup used to relate the different data objects that make up a complete L1 product.

Vgroup Name	Vgroup Class	Object Name	Type	Description
Scene_Data_Ref	Image_Data	L71ppprrr_rrrYYYYMMDD.B10	SDS	ETM+ band 1 data
		L71ppprrr_rrrYYYYMMDD.B20	SDS	ETM+ band 2 data
		L71ppprrr_rrrYYYYMMDD.B30	SDS	ETM+ band 3 data
		L71ppprrr_rrrYYYYMMDD.B40	SDS	ETM+ band 4 data
		L71ppprrr_rrrYYYYMMDD.B50	SDS	ETM+ band 5 data
		L72ppprrr_rrrYYYYMMDD.B70	SDS	ETM+ band 7 data
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
Scene_Data_Thm	Image_Data	L71ppprrr_rrrYYYYMMDD.B60	SDS	ETM+ band 6-low gain data
		L72ppprrr_rrrYYYYMMDD.B60	SDS	ETM+ band 6-high gain data
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
Scene_Data_Pan	Image_Data	L72ppprrr_rrrYYYYMMDD.B80	SDS	ETM+ band 8 data
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
IC_Data_Ref	Correction_Data	L71ppprrr_rrrYYYYMMDD.C10	SDS	IC data band 1
		L71ppprrr_rrrYYYYMMDD.C20	SDS	IC data band 2
		L71ppprrr_rrrYYYYMMDD.C30	SDS	IC data band 3
		L71ppprrr_rrrYYYYMMDD.C40	SDS	IC data band 4
		L71ppprrr_rrrYYYYMMDD.C50	SDS	IC data band 5
		L72ppprrr_rrrYYYYMMDD.C70	SDS	IC data band 7
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
IC_Data_Thm	Correction_Data	L71ppprrr_rrrYYYYMMDD.C60	SDS	IC data band 6-low gain
		L72ppprrr_rrrYYYYMMDD.C60	SDS	IC data band 6-high gain
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
IC_Data_Pan	Correction_Data	L72ppprrr_rrrYYYYMMDD.C80	SDS	IC data band 8
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
Scan_Line_Offset s_Ref	Correction_Data	L71ppprrr_rrrYYYYMMDD.O10	Vdata	Scan line offsets band 1
		L71ppprrr_rrrYYYYMMDD.O20	Vdata	Scan line offsets band 2
		L71ppprrr_rrrYYYYMMDD.O30	Vdata	Scan line offsets band 3
		L71ppprrr_rrrYYYYMMDD.O40	Vdata	Scan line offsets band 4
		L71ppprrr_rrrYYYYMMDD.O50	Vdata	Scan line offsets band 5
		L72ppprrr_rrrYYYYMMDD.O70	Vdata	Scan line offsets band 7
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
Scan_Line_Offset s_Thm	Correction_Data	L71ppprrr_rrrYYYYMMDD.O60	Vdata	Scan line offsets band 6-low gain
		L72ppprrr_rrrYYYYMMDD.O60	Vdata	Scan line offsets band 6-high gain
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
Scan_Line_Offset s_Pan	Correction_Data	L72ppprrr_rrrYYYYMMDD.O80	Vdata	Scan line offsets band 8
		L71ppprrr_rrrYYYYMMDD.GEO	Vdata	Geolocation table
PCD	Correction_Data	L71ppprrr_rrrYYYYMMDD.PCD	Vdata	Consensus PCD
MSCD	Correction_Data	L71ppprrr_rrrYYYYMMDD.MSD	Vdata	Consensus MSCD
Product_Metadata	Metadata	L71ppprrr_rrrYYYYMMDD.MTA	Vdata	LPS metadata format 1
		L72ppprrr_rrrYYYYMMDD.MTA	Vdata	LPS metadata format 2
		L71ppprrr_rrrYYYYMMDD.MTL	Vdata	Level 1-product-specific metadata
CPF	Correction_Data	L7CPFYYYYMMDD_YYYYMMDD_nn	Vdata	IAS CPF

Table 3-12. Vgroup Definitions: Level 1R Product

Vgroup Name	Vgroup Class	Object Name	Type	Description
Scene_Data_Ref	Image_Data	L71pppprrr_rrrYYYYMMDD.B10	SDS	ETM+ band 1 data
		L71pppprrr_rrrYYYYMMDD.B20	SDS	ETM+ band 2 data
		L71pppprrr_rrrYYYYMMDD.B30	SDS	ETM+ band 3 data
		L71pppprrr_rrrYYYYMMDD.B40	SDS	ETM+ band 4 data
		L71pppprrr_rrrYYYYMMDD.B50	SDS	ETM+ band 5 data
		L72pppprrr_rrrYYYYMMDD.B70	SDS	ETM+ band 7 data
Scene_Data_Thm	Image_Data	L71pppprrr_rrrYYYYMMDD.B60	SDS	ETM+ band 6-low gain data
		L72pppprrr_rrrYYYYMMDD.B60	SDS	ETM+ band 6-high gain data
Scene_Data_Pan	Image_Data	L72pppprrr_rrrYYYYMMDD.B80	SDS	ETM+ band 8 data
Product_Metadata	Metadata	L71pppprrr_rrrYYYYMMDD.MTL	Vdata	Level 1-product-specific metadata

Table 3-13. Vgroup Definitions: Level 1G Product

3.3.2 Level 1 Metadata File

The L1 metadata file is created during product generation and contains information specific to the product ordered. Table 3-14 lists the full contents of the L1 metadata file. This file contains all applicable image description information from the L0Rp metadata file and the Landsat Processing System (LPS) metadata provided with the L0Rp product.

Vdata Name: L71pppprrr_rrrYYYYMMDD.MTL
Vdata Class: LPGS_Metadata
Interlace Type: FULL_INTERLACE
Bytes Per Logical Record: 65535
Number of Records: One record

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
GROUP	18	= L1_METADATA_FILE	Beginning of first-level Object Description Language (ODL) group; indicates the start of the L1 metadata file level group
GROUP	18	= METADATA_FILE_INFO	Beginning of the metadata file information group
ORIGIN	47	= "Image courtesy of the U.S. Geological Survey"	Establishes the origin of the image to be from the USGS.
REQUEST_ID	20	USGS products use the NNNYYMMDDSSSS_UUUUU format, where: NNNYYMMDDSSSS = 13-digit DORRAN order number NNN = Node indicator YY = Year MM = Month DD = Day SSSS = Sequence number for the day UUUUU = 5-digit DORRAN unit	Data producer-defined request number that uniquely identifies each product; USGS products use a unique product generation DORRAN-generated request ID

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		number	
PRODUCT_CREATION_TIME	20	= YYYY-MM-DDThh:mm:ssZ where: YYYY = 4-digit Julian year MM = month number of Julian year (01-12) DD = day of Julian month (01-31) T = start of time information in ODL ASCII time code format hh = hours (00-23) mm = minutes (00-59) ss = seconds (00-59) Z = Zulu time (same as GMT)	L1 system date and time when metadata file for L1 product set was created; for ease of human readability, this date and time are presented in ODL ASCII format; time is expressed as Universal Time Coordinated (UTC) (also known as Greenwich Mean Time [GMT]) Insertion of additional characters "T" and "Z" is required to meet ODL ASCII format
STATION_ID	3	= "EDC"	Unique 3-letter code identifying originating ground station
LANDSAT7_XBAND	1	= "0", "1", "2", or "3" (0 = unknown)	L7 X-band used to downlink data to LGS
GROUND_STATION	3	= "NNN"	Ground station that received data
LPS_PROCESSOR_NUMBER	1	= "1" through "9"	LPS processor number
DATEHOURL_CONTACT_PERIOD	7	= "YYDOYHH"	Date and hour of contact period
SUBINTERVAL_NUMBER	2	= "00" through "99"	Subinterval number within contact period
END_GROUP	18	= METADATA_FILE_INFO	End of metadata information group
GROUP	16	= PRODUCT_METADATA	Beginning of product metadata group
PRODUCT_TYPE	4	= "L1Gt"	Identifier to inform user of product type
	3	= "L1G" = "L1R" = "L1P" (NLAPS only) = "L1T"	
ELEVATION_SOURCE	7	= "NED" = "SRTM" = "GTOPO30"	Identifies the digital elevation dataset that was used to terrain correct the product.
PROCESSING_SOFTWARE	15	= "SYSTEM_VERSION" where: SYSTEM = IAS, LPGS, NLAPS VERSION = version of software	L1 processing system and software version Examples: IAS_4.5 LPGS_4.3 NLAPS_4.1.9
EPHEMERIS_TYPE	10	= "DEFINITIVE" = "PREDICTIVE"	Identifier to inform the user of the orbital ephemeris type used; if the field is not present, the user should

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			assume "PREDICTIVE" in all cases (1G product only)
SPACECRAFT_ID	8	= "Landsat7"	Name of satellite platform
SENSOR_ID	4	= "ETM+"	Name of imaging sensor
SENSOR_MODE	6	= SAM = BUMPER	Scan Angle Monitor Mode (SAM) and Bumper Mode (BUMPER).
ACQUISITION_DATE	20	= YYYY-MM-DD	Date the image was acquired
SEGMENT_ACQ_DATE	10	= YYYY-MM-DD	Acquisition date of the scene used for segment map generation (1 scene only). Only included for phase 3 gap filled products (L1T_SEG products).
GAP_FILL_ACQ_DATE	56	= (YYYY-MM-DD,YYYY-MM-DD,YYYY-MM-DD,YYYY-MM-DD)	Acquisition date of input scenes used for scan gap-fill (up to five input scenes) Note: Only included with gap-filled products
REGISTRATION_ACQ_DATE	10	= YYYY-MM-DD	Acquisition date of the scene used for registration (one scene only); only included for gap-filled products
WRS_PATH	3	= NNN, where NNN = path number (001-233)	WRS path value for product
STARTING_ROW	3	= NNN, where NNN = row of first full or partial scene in product (001-248)	Starting WRS row
ENDING_ROW	3	= NNN, where NNN = row of last full or partial scene in product (001-248)	Ending WRS row
BAND_COMBINATION	9	= NNNNNNNNN, where NNNNNNNNN = e.g., 123456678 for all bands present, 123-----8 for bands 1, 2, 3, 8; a "-" is a position holder for absent bands	L1-generated indicator of bands present for the product ordered; first 6 is format 1, band 6; second 6 is format 2, band 6
PRODUCT_UL_CORNER_LAT	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision) Positive (+) value indicates north latitude; negative (-) value indicates south latitude	Latitude value for the upper-left corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_UL_CORNER_LON	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision) Positive (+) value indicates east longitude; negative (-) value	Longitude value for the upper-left corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		indicates west longitude	
PRODUCT_UR_CORNER_LAT	11	= –90.0000000 through +90.0000000 degrees (with 7-digit precision)	Latitude value for the upper-right corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_UR_CORNER_LON	12	= –180.0000000 through +180.0000000 degrees (with 7-digit precision)	Longitude value for the upper-right corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_LL_CORNER_LAT	11	= –90.0000000 through +90.0000000 degrees (with 7-digit precision)	Latitude value for the lower-left corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_LL_CORNER_LON	12	= –180.0000000 through +180.0000000 degrees (with 7-digit precision)	Longitude value for the lower-left corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_LR_CORNER_LAT	11	= –90.0000000 through +90.0000000 degrees (with 7-digit precision)	Latitude value for the lower-right corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_LR_CORNER_LON	12	= –180.0000000 through +180.0000000 degrees (with 7-digit precision)	Longitude value for the lower-right corner of the product (L1 systems recalculate for 1G product) (NLAPS bands 1-5, 7 only)
PRODUCT_UL_CORNER_MAPX	14	= –132000000.000 through 132000000.000 Units are feet or meters	Projection X coordinate for the upper-left corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_UL_CORNER_MAPY	14	= –132000000.000 through 132000000.000 Units are feet or meters	Projection Y coordinate for the upper-left corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_UR_CORNER_MAPX	14	= –132000000.000 through 132000000.000 Units are feet or meters	Projection X coordinate for the upper-right corner of the product (L1 systems calculated, 1G only)

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			(NLAPS bands 1-5, 7 only)
PRODUCT_UR_CORNER_MAP_Y	14	= -132000000.000 through 132000000.000 Units are feet or meters	Projection Y coordinate for the upper-right corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_LL_CORNER_MAPX	14	= -132000000.000 through 132000000.000 Units are feet or meters	Projection X coordinate for the lower-left corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_LL_CORNER_MAPY	14	= -132000000.000 through 132000000.000 Units are feet or meters	Projection Y coordinate for the lower-left corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_LR_CORNER_MAPX	14	= -132000000.000 through 132000000.000 Units are feet or meters	Projection X coordinate for the lower-right corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_LR_CORNER_MAPY	14	= -132000000.000 through 132000000.000 Units are feet or meters	Projection Y coordinate for the lower-right corner of the product (L1 systems calculated, 1G only) (NLAPS bands 1-5, 7 only)
PRODUCT_UL_CORNER_LAT_PAN	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision) Positive (+) value indicates north latitude; negative (-) value indicates south latitude	NLAPS latitude value for the upper-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_LON_PAN	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision) Positive (+) value indicates East longitude; negative (-) value indicates West longitude	NLAPS longitude value for the upper-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_LAT_PAN	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision)	NLAPS latitude value for the upper-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_LON_PAN	12	= -180.0000000 through +180.0000000 degrees (with 7-digit	NLAPS longitude value for the upper-right corner of

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		precision)	product band 8 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_LAT_PAN	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision)	NLAPS latitude value for the lower-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_LON_PAN	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision)	NLAPS longitude value for the lower-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_LAT_PAN	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision)	NLAPS latitude value for the lower-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_LON_PAN	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision)	NLAPS longitude value for the lower-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_MAPX_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the upper-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_MAPY_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the upper-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_MAPX_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the upper-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_MAPY_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the upper-right corner of product band 8 (Not included with IAS and

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			LPGS)
PRODUCT_LL_CORNER_MAPX_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the lower-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_MAPY_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the lower-left corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_MAPX_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the lower-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_MAPY_PAN	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the lower-right corner of product band 8 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_LAT_THM	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision) Positive (+) value indicates north latitude; negative (-) value indicates south latitude	NLAPS latitude value for the upper-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_LON_THM	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision) Positive (+) value indicates east longitude; negative (-) value indicates west longitude	NLAPS longitude value for the upper-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_LAT_THM	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision)	NLAPS latitude value for the upper-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_LON_THM	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision)	NLAPS longitude value for the upper-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_LAT_THM	11	= -90.0000000 through +90.0000000 degrees (with 7-digit	NLAPS latitude value for the lower-left corner of product

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		precision)	bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_LON_THM	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision)	NLAPS longitude value for the lower-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_LAT_THM	11	= -90.0000000 through +90.0000000 degrees (with 7-digit precision)	NLAPS latitude value for the lower-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_LON_THM	12	= -180.0000000 through +180.0000000 degrees (with 7-digit precision)	NLAPS longitude value for the lower-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_MAPX_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the upper-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UL_CORNER_MAPY_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the upper-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_MAPX_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the upper-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_UR_CORNER_MAPY_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the upper-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_MAPX_THM	14	= -132000000.000 through 132000000.000	NLAPS projection X coordinate for the lower-left corner of product bands 61,

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		Units are feet or meters	62 (Not included with IAS and LPGS)
PRODUCT_LL_CORNER_MAPY_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the lower-left corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_MAPX_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection X coordinate for the lower-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_LR_CORNER_MAPY_THM	14	= -132000000.000 through 132000000.000 Units are feet or meters	NLAPS projection Y coordinate for the lower-right corner of product bands 61, 62 (Not included with IAS and LPGS)
PRODUCT_SAMPLES_PAN	6		Product samples for the panchromatic band
PRODUCT_LINES_PAN	6		Product lines for the panchromatic band
PRODUCT_SAMPLES_REF	6		Product samples for the reflective bands
PRODUCT_LINES_REF	6		Product lines for the reflective bands
PRODUCT_SAMPLES_THM	6		Product samples for the thermal bands
PRODUCT_LINES_THM	6		Product lines for the thermal bands
BAND1_FILE_NAME	29	"L71pprrr_rrrYYYYMMDD_B10.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 1, if part of the product
BAND2_FILE_NAME	29	"L71pprrr_rrrYYYYMMDD_B20.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 2, if part of the product
BAND3_FILE_NAME	29	"L71pprrr_rrrYYYYMMDD_B30.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 3, if part of the product
BAND4_FILE_NAME	29	"L71pprrr_rrrYYYYMMDD_B40.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 4, if part of the product

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
BAND5_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_B50.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 5, if part of the product
BAND61_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_B61.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 6 format 1, if part of the product
BAND62_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_B62.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 6 format 2, if part of the product
BAND7_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_B70.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 7, if part of the product
BAND8_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_B80.XXX" (XXX = L1R, L1G, TIF, or FST)	L1-generated external element file name for band 8, if part of the product
IC_DATA_F1_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_CAL.XXX" (XXX = L1R)	L1-generated external element file name for format 1 internal calibrator data (1R product only), if part of the product
IC_DATA_F2_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_CAL.XXX" (XXX = L1R)	L1-generated external element file name for format 2 internal calibrator data (1R product only), if part of the product
SCAN_SHIFTS_F1_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_SLO.XXX" (XXX = L1R)	L1-generated external element file name for format 1 scan line shifts (1R product only), if part of the product
SCAN_SHIFTS_F2_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_SLO.XXX" (XXX = L1R)	L1-generated external element file name for format 2 scan line shifts (1R product only), if part of the product
MSCD_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_MSD.XXX" (XXX = L1R)	L1-generated external element file name for consensus MSCD (1R product only)
PCD_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_PCD.XXX" (XXX = L1R)	L1-generated external element file name for consensus PCD (1R product only)
METADATA_LPS1_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_MTA.txt" (XXX = L1R)	L1-generated external element file name for LPS format 1 metadata (1R product only)
METADATA_LPS2_FILE_NAME	29	"L72ppprrr_rrrYYYYMMDD_MTA.t	L1-generated external

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		xt" (XXX = L1R)	element file name for LPS format 2 metadata (1R product only)
METADATA_L1_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_MTL.tx t"	L1-generated external element file name for L1 metadata
CPF_FILE_NAME	25	"L7CPFYYYYMMDD_YYYYMMDD _nn" where: YYYYMMDD = effective start date and effective end date, respectively nn = incrementing version number within a 90-day period (00-99)	Archive-generated external element file name for IAS CPF NLAPS populates the metadata file with the CPF used during processing
GEOLOCATION_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_GEO. XXX" (XXX = L1R)	L1-generated external element file name for the geolocation table (1R product only)
HDF_DIR_FILE_NAME	29	"L71ppprrr_rrrYYYYMMDD_HDF.X XX" (XXX = L1R, L1G, L1P, or L1T)	L1-generated file name for the HDF directory file (HDF products only)
END_GROUP	16	= PRODUCT_METADATA	End of product metadata group
GROUP	16	= MIN_MAX_RADIANCE	Beginning of the minimum/maximum radiance group (1G product only)
LMAX_BAND1	7	= NNN.NNN	Maximum achievable spectral radiance value for band 1, if part of the product (w/[m ² sr micron]); the spectral radiance corresponding to QCALMAX_BAND1
LMIN_BAND1	7	= NNN.NNN	Minimum achievable spectral radiance value for band 1, if part of the product (w/[m ² sr micron]); the spectral radiance corresponding to QCALMIN_BAND1
LMAX_BAND2	7	= NNN.NNN	Maximum achievable spectral radiance value for band 2, if part of the product (w/[m ² sr micron]); the spectral radiance corresponding to QCALMAX_BAND2
LMIN_BAND2	7	= NNN.NNN	Minimum achievable spectral radiance value for band 2, if part of the product (w/[m ² sr micron]); the

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			spectral radiance corresponding to QCALMIN_BAND2
LMAX_BAND3	7	= NNN.NNN	Maximum achievable spectral radiance value for band 3, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMAX_BAND3
LMIN_BAND3	7	= NNN.NNN	Minimum achievable spectral radiance value for band 3, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMIN_BAND3
LMAX_BAND4	7	= NNN.NNN	Maximum achievable spectral radiance value for band 4, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMAX_BAND4
LMIN_BAND4	7	= NNN.NNN	Minimum achievable spectral radiance value for band 4, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMIN_BAND4
LMAX_BAND5	7	= NNN.NNN	Maximum achievable spectral radiance value for band 5, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMAX_BAND5
LMIN_BAND5	7	= NNN.NNN	Minimum achievable spectral radiance value for band 5, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMIN_BAND5
LMAX_BAND61	7	= NNN.NNN	Maximum achievable spectral radiance value for band 6 format 1, if part of the product (w/[m^2 sr micron]); the spectral radiance corresponding to QCALMAX_BAND61
LMIN_BAND61	7	= NNN.NNN	Minimum achievable

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			spectral radiance value for band 6 format 1, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMIN_BAND61
LMAX_BAND62	7	= NNN.NNN	Maximum achievable spectral radiance value for band 6 format 2, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMAX_BAND62
LMIN_BAND62	7	= NNN.NNN	Minimum achievable spectral radiance value for band 6 format 2, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMIN_BAND62
LMAX_BAND7	7	= NNN.NNN	Maximum achievable spectral radiance value for band 7, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMAX_BAND7
LMIN_BAND7	7	= NNN.NNN	Minimum achievable spectral radiance value for band 7, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMIN_BAND7
LMAX_BAND8	7	= NNN.NNN	Maximum achievable spectral radiance value for band 8, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMAX_BAND8
LMIN_BAND8	7	= NNN.NNN	Minimum achievable spectral radiance value for band 8, if part of the product ($w/[m^2 \text{ sr micron}]$); the spectral radiance corresponding to QCALMIN_BAND8
END_GROUP	16	= MIN_MAX_RADIANCE	End of the minimum/maximum radiance group
GROUP	19	= MIN_MAX_PIXEL_VALUE	Beginning of the minimum/maximum pixel

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			value group (1G product only)
QCALMAX_BAND1	5	= NNN.N	Maximum possible pixel value for band 1, if part of the product (Digital Number [DN])
QCALMIN_BAND1	5	= NNN.N	Minimum possible pixel value for band 1, if part of the product (DN)
QCALMAX_BAND2	5	= NNN.N	Maximum possible pixel value for band 2, if part of the product (DN)
QCALMIN_BAND2	5	= NNN.N	Minimum possible pixel value for band 2, if part of the product (DN)
QCALMAX_BAND3	5	= NNN.N	Maximum possible pixel value for band 3, if part of the product (DN)
QCALMIN_BAND3	5	= NNN.N	Minimum possible pixel value for band 3, if part of the product (DN)
QCALMAX_BAND4	5	= NNN.N	Maximum possible pixel value for band 4, if part of the product (DN)
QCALMIN_BAND4	5	= NNN.N	Minimum possible pixel value for band 4, if part of the product (DN)
QCALMAX_BAND5	5	= NNN.N	Maximum possible pixel value for band 5, if part of the product (DN)
QCALMIN_BAND5	5	= NNN.N	Minimum possible pixel value for band 5, if part of the product (DN)
QCALMAX_BAND61	5	= NNN.N	Maximum possible pixel value for band 6 format 1, if part of the product (DN)
QCALMIN_BAND61	5	= NNN.N	Minimum possible pixel value for band 6 format 1, if part of the product (DN)
QCALMAX_BAND62	5	= NNN.N	Maximum possible pixel value for band 6 format 2, if part of the product (DN)
QCALMIN_BAND62	5	= NNN.N	Minimum possible pixel value for band 6 format 2, if part of the product (DN)
QCALMAX_BAND7	5	= NNN.N	Maximum possible pixel value for band 7, if part of the product (DN)
QCALMIN_BAND7	5	= NNN.N	Minimum possible pixel value for band 7, if part of the product (DN)
QCALMAX_BAND8	5	= NNN.N	Maximum possible pixel value for band 8, if part of

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			the product (DN)
QCALMIN_BAND8	5	= NNN.N	Minimum possible pixel value for band 8, if part of the product (DN)
END_GROUP	19	= MIN_MAX_PIXEL_VALUE	End of the minimum/maximum pixel value group
GROUP	18	= PRODUCT_PARAMETERS	Beginning of product parameters group (both 1R and 1G products)
CORRECTION_METHOD_GAIN_BAND1	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 1, if part of the product
CORRECTION_METHOD_GAIN_BAND2	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 2, if part of the product
CORRECTION_METHOD_GAIN_BAND3	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 3, if part of the product
CORRECTION_METHOD_GAIN_BAND4	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 4, if part of the product
CORRECTION_METHOD_GAIN_BAND5	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 5, if part of the product
CORRECTION_METHOD_GAIN_BAND61	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 6 format 1, if part of the product
CORRECTION_METHOD_GAIN_BAND62	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 6 format 2, if part of the product
CORRECTION_METHOD_GAIN_BAND7	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 7, if part of the product
CORRECTION_METHOD_GAIN_BAND8	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image for band 8, if part of the product
CORRECTION_METHOD_BIAS	3	= "CPF" (for CPF gains) = "IC" (for IC gains)	Correction method used by L1 in creating the image
BAND1_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 1's first data line, if part of the product
BAND2_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 2's first data line, if part of the product
BAND3_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 3's first data line, if part of the product
BAND4_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 4's first data line, if part of the

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			product
BAND5_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 5's first data line, if part of the product
BAND6_GAIN1	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 6's first data line, if part of the product-format 1
BAND6_GAIN2	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 6's first data line, if part of the product-format 2
BAND7_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 7's first data line, if part of the product
BAND8_GAIN	1	= "L" (for low gain) = "H" (for high gain)	Gain state for band 8's first data line, if part of the product
BAND1_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 1, if part of the product
BAND2_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 2, if part of the product
BAND3_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 3, if part of the product
BAND4_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 4, if part of the product
BAND5_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 5, if part of the product
BAND6_GAIN_CHANGE1	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 6 format 1, if part of the product
BAND6_GAIN_CHANGE2	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 6 format 2, if part of the product
BAND7_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 7, if part of the product
BAND8_GAIN_CHANGE	1	= "0" (for no gain change) = "+" (for low to high) = "-" (for high to low)	Presence and direction of gain change for band 8, if part of the product
BAND1_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND2_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			change actually occurred in the previous scan
BAND3_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND4_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND5_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND6_SL_GAIN_CHANGE1	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND6_SL_GAIN_CHANGE2	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND7_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
BAND8_SL_GAIN_CHANGE	1-5	= 0 (for no gain change) = 1-12000 (for the scan line number)	Scan line number, where the first change in band gain was detected; physical change actually occurred in the previous scan
SUN_AZIMUTH	12	= -180.0000000 through 180.0000000 degrees (with 7-digit precision) A positive value (+) indicates angles to the east or clockwise from the north. A negative value (–) indicates angles to the west or counterclockwise from the north. Leading zeros are not required.	Sun azimuth angle in degrees for image center location at image center acquisition time
SUN_ELEVATION	11	= -90.0000000 through 90.0000000 degrees (with 7-digit precision)	Sun elevation angle in degrees for image center location at image center

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
		A positive value (+) indicates a day-time scene. A negative value (–) indicates a night-time scene. Leading zeros are not required.	acquisition time
OUTPUT_FORMAT	10	= "FORMAT_VERSION" where: FORMAT = HDF, NDF, GEOTIFF, FASTL7A VERSION = output format version	Output format and output format version of image Examples: HDF_4r1 NDF_2.00 GEOTIFF FASTL7A Note: No version included for GEOTIFF and FASTL7A
END_GROUP	18	= PRODUCT_PARAMETERS	End of product parameters group
GROUP	19	= CORRECTIONS_APPLIED	Beginning of corrections applied group
STRIPING_BAND1	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 1 image, if part of the product NLAPS: BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND2	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 2 image, if part of the product NLAPS: BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND3	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 3 image, if part of the product NLAPS: BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND4	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 4 image, if part of the product NLAPS: BAND_AVERAGE = NASA

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			REFERENCE_DETECTOR = CCRS
STRIPING_BAND5	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 5 image, if part of the product <u>NLAPS:</u> BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND61	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 6 format 1 image, if part of the product <u>NLAPS:</u> BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND62	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 6 format 2 image, if part of the product <u>NLAPS:</u> BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND7	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 7 image, if part of the product <u>NLAPS:</u> BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
STRIPING_BAND8	20	= "NONE" = "BAND_AVERAGE" = "REFERENCE_DETECTOR"	Indicator of type of striping correction applied for band 8 image, if part of the product <u>NLAPS:</u> BAND_AVERAGE = NASA REFERENCE_DETECTOR = CCRS
BANDING	1	= "Y" or "N"	Indicator of whether the image was corrected for banding
COHERENT_NOISE	1	= "Y" or "N"	Indicator of whether the image was corrected for coherent noise (band 8 only)
MEMORY_EFFECT	1	= "Y" or "N"	Indicator of whether the image was corrected for memory effect

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
SCAN_CORRELATED_SHIFT	1	= "Y" or "N"	Indicator of whether the image was corrected for scan correlated shift
INOPERABLE_DETECTORS	1	= "Y" or "N"	Indicator of whether the image was corrected for inoperable detectors
DROPPED_LINES	1	= "Y" or "N"	Indicator of whether the image was corrected for dropped lines
END_GROUP	19	= CORRECTIONS_APPLIED	End of corrections applied group
GROUP	21	= PROJECTION_PARAMETERS	Beginning of projection parameters group (1G product only)
REFERENCE_DATUM	5	= "WGS84"	Datum used in creating the image
REFERENCE_ELLIPSOID	5	= "WGS84"	Ellipsoid used in creating the image
GRID_CELL_SIZE_PAN	6	= 5.00–60.000 m, in increments of 0.001 m 14.25–60.00 m (IAS/LPGS) 5.00–50.00 m (NLAPS)	Grid cell size used in creating the image for pan band, if part of the product
GRID_CELL_SIZE_THM	6	= 10.0–100.00 m, in increments of 0.001 m 25.00–60.00 m (IAS/LPGS) 10.00–100.00 m (NLAPS)	Grid cell size used in creating the image for thermal bands, if part of the product
GRID_CELL_SIZE_REF	6	= 10.00–60.000 m, in increments of 0.001 m 25.00–60.00 m (IAS/LPGS) 10.00–50.00 m (NLAPS)	Grid cell size used in creating the image for VNIR/SWIR bands, if part of the product
ORIENTATION	3	= "NOM" (Nominal Path) = "NUP" (North Up) = "TN" (True North*) = "USR" (User*)	Orientation used in creating the image *NLAPS Only
RESAMPLING_OPTION	3	= "NN" (Nearest Neighbor) = "CC" (Cubic Convolution) = "MTF" (Modulation Transfer Function*) = "BI" (Bilinear**) = "KD" (Kaiser Damped**) = "16" (16-Point Sinc**) = "8" (8-Point Sinc**) = "DW" (Damped Window**)	Resampling option used in creating the image * IAS/LPGS Only ** NLAPS Only
SCAN_GAP_INTERPOLATION	4	= 00.0–15.0	Maximum scan gap width to fill by interpolation, in units of ETM+ 30-m detectors/pixels Note: Only included with single SLC-off and gap-filled

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			products
MAP_PROJECTION	4	= "AKC" (Alaska Conformal*) = "AEA" (Albers Equal Area) = "AZIM" (Azimuthal*) = "EQC" (Equidistant Conic [Type A & B]*) = "EQUI" (Equirectangular*) = "GVNP" (General Vertical Near Side Perspective*) = "GNOM" (Gnomonic*) = "HAMM" (Hammer*) = "IGH" (Interrupted Goodes Homolosine*) = "IM" (Interrupted Mollweide*) = "LAEA" (Lambert Azimuthal Equal Area*) = "LCC" (Lambert Conformal Conic) = "MERC" (Mercator*) = "MCYL" (Miller Cylindrical*) = "MOLL" (Mollweide*) = "OEA" (Oblated Equal Area*) = "OM" (Oblique Mercator [Type A and B]) = "ORTH" (Orthographic*) = "PC" (Polyconic) = "PS" (Polar Stereographic) = "ROBN" (Robinson*) = "SINU" (Sinusoidal*) = "SOM" (Space Oblique Mercator [Type A* and B]) = "STPL" (State Plane*) = "STRG" (Stereographic*) = "TM" (Transverse Mercator [Gauss-Krueger]) = "UTM" (Universal Transverse Mercator) = "VDGR" (Van Der Grinten*) = "WIV" (Wagner IV*) = "WVII" (Wagner VII*)	Map projection used in creating the image *NLAPS Only
END_GROUP	21	= PROJECTION_PARAMETERS	End of projection parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of AKC
GROUP	14	AKC_PARAMETERS	Beginning of AKC parameters group
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for AKC projection
END_GROUP	14	AKC_PARAMETERS	End of AKC parameters

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of AEA
GROUP	14	AEA_PARAMETERS	Beginning of AEA parameters group
LATITUDE_OF_FIRST_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of first standard parallel
LATITUDE_OF_SECOND_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of second standard parallel
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for AEA projection
END_GROUP	14	AEA_PARAMETERS	End of AEA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of AZIM
GROUP	15	AZIM_PARAMETERS	Beginning of AZIM parameters group
LONGITUDE_OF_CENTER	12	= -180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= -90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for AZIM projection
END_GROUP	15	AZIM_PARAMETERS	End of AZIM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of EQC
GROUP	14	EQC_PARAMETERS	Beginning of EQC parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for EQC projection
EQC_TYPE	1	= "A" or "B"	Value used to indicate type

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			of EQC projection
END_GROUP	14	EQC_PARAMETERS	End of EQC parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of EQCA
GROUP	15	EQCA_PARAMETERS	Beginning of EQCA parameters group
LATITUDE_OF_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of standard parallel
END_GROUP	15	EQCA_PARAMETERS	End of EQCA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of EQCB
GROUP	15	EQCB_PARAMETERS	Beginning of EQCB parameters group
LATITUDE_OF_FIRST_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of first standard parallel
LATITUDE_OF_SECOND_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of second standard parallel
END_GROUP	15	EQCB_PARAMETERS	End of EQCB parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of EQUI
GROUP	15	EQUI_PARAMETERS	Beginning of EQUI parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_TRUE_SCALE	11	= -90.0 to +90.0	Latitude of true scale
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for EQUI projection
END_GROUP	15	EQUI_PARAMETERS	End of EQUI parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of GNOM
GROUP	15	GNOM_PARAMETERS	Beginning of GNOM parameters group
LONGITUDE_OF_CENTER	12	= -180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= -90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
FALSE_EASTING_NORTHING_UNITS	6	= “meters” or “feet”	Units for false easting and northing for GNOM projection
END_GROUP	15	GNOM_PARAMETERS	End of GNOM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of GVNP
GROUP	15	GVNP_PARAMETERS	Beginning of GVNP parameters group
HEIGHT	38	= 0 to	Height of perspective point in meters
LONGITUDE_OF_CENTER	12	= –180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= –90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= “meters” or “feet”	Units for false easting and northing for GVNP projection
END_GROUP	15	GVNP_PARAMETERS	End of GVNP parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of HAMM
GROUP	15	HAMM_PARAMETERS	Beginning of HAMM parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= –180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= “meters” or “feet”	Units for false easting and northing for HAMM projection
END_GROUP	15	HAMM_PARAMETERS	End of HAMM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of LAEA
GROUP	15	LAEA_PARAMETERS	Beginning of LAEA parameters group
LONGITUDE_OF_CENTER	12	= –180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= –90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= “meters” or “feet”	Units for false easting and

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
UNITS			northing for LAEA projection
END_GROUP	15	LAEA_PARAMETERS	End of LAEA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of LCC
GROUP	14	LCC_PARAMETERS	Beginning of LCC parameters group
LATITUDE_OF_FIRST_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of first standard parallel
LATITUDE_OF_SECOND_STANDARD_PARALLEL	11	= -90.0 to +90.0	Latitude of second standard parallel
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for LCC projection
END_GROUP	14	LCC_PARAMETERS	End of LCC parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of MERC
GROUP	15	MERC_PARAMETERS	Beginning of MERC parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_TRUE_SCALE	11	= -90.0 to +90.0	Latitude of true scale
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for MERC projection
END_GROUP	15	MERC_PARAMETERS	End of MERC parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of MCYL
GROUP	15	MCYL_PARAMETERS	Beginning of MCYL parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for MCYL projection
END_GROUP	15	MCYL_PARAMETERS	End of MCYL parameters

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of MOLL
GROUP	15	MOLL_PARAMETERS	Beginning of MOLL parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for MOLL projection
END_GROUP	15	MOLL_PARAMETERS	End of MOLL parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of OEA
GROUP	14	OEA_PARAMETERS	Beginning of OEA parameters group
HORIZONTAL_FLATNESS			Horizontal flatness of the oblong region
VERTICAL_FLATNESS			Vertical flatness of the oblong region
LONGITUDE_OF_CENTER	12	= -180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= -90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for OEA projection
ANGLE		= 0 to 360	Direction of an axis of the oblong region
END_GROUP	14	OEA_PARAMETERS	End of OEA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of OM
GROUP	13	OM_PARAMETERS	Beginning of OM parameters group
SCALE_FACTOR_AT_CENTER_OF_PROJECTION	9	= 0.0 to 2.0	Scale factor at center of projection
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for OM projection
OM_TYPE	1	= "A" or "B"	Value used to indicate type

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
			of OM projection
END_GROUP	13	OM_PARAMETERS	End of OM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of Oblique Mercator, Type A (OMA)
GROUP	14	OMA_PARAMETERS	Beginning of OMA parameters group
LONGITUDE_FIRST_POINT_GEODETTIC	12	= -180.0 to +180.0	Longitude of first point defining central geodetic line of projection
LATITUDE_FIRST_POINT_GEODETTIC	11	= -90.0 to +90.0	Latitude of first point defining central geodetic line of projection
LONGITUDE_SECOND_POINT_GEODETTIC	12	= -180.0 to +180.0	Longitude of second point defining central geodetic line of projection
LATITUDE_SECOND_POINT_GEODETTIC	11	= -90.0 to +90.0	Latitude of second point defining central geodetic line of projection
END_GROUP	14	OMA_PARAMETERS	End of OMA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of OMB
GROUP	14	OMB_PARAMETERS	Beginning of OMB parameters group
ANGLE_OF_AZIMUTH	12	= -180.0 to +180.0	Angle of azimuth east of north for central line of projection
LONGITUDE_ALONG_PROJECTION	12	= -180.0 to +180.0	Longitude of point along central line of projection at which angle of azimuth is measured
END_GROUP	14	OMB_PARAMETERS	End of OMB parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of ORTH
GROUP	15	ORTH_PARAMETERS	Beginning of ORTH parameters group
LONGITUDE_OF_CENTER	12	= -180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= -90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_	6	= "meters" or "feet"	Units for false easting and

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
UNITS			northing for ORTH projection
END_GROUP	15	ORTH_PARAMETERS	End of ORTH parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of PC
GROUP	13	PC_PARAMETERS	Beginning of PC parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for PC projection
END_GROUP	13	PC_PARAMETERS	End of PC parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of PS
GROUP	13	PS_PARAMETERS	Beginning of PS parameters group
VERTICAL_LONGITUDE_FROM_POLE	12	= -180.0 to +180.0	Vertical longitude from pole
LATITUDE_OF_TRUE_SCALE	11	= -90.0 to +90.0	Latitude of true scale
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for PS projection
END_GROUP	13	PS_PARAMETERS	End of PS parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of ROBN
GROUP	15	ROBN_PARAMETERS	Beginning of ROBN parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for ROBN projection
END_GROUP	15	ROBN_PARAMETERS	End of ROBN parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of SINU

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
GROUP	15	SINU_PARAMETERS	Beginning of SINU parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for SINU projection
END_GROUP	15	SINU_PARAMETERS	End of SINU parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of SOM
GROUP	14	SOM_PARAMETERS	Beginning of SOM parameters group
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for SOM projection
SOM_TYPE	1	= "A" or "B"	Value used to indicate type of SOM projection
END_GROUP	14	SOM_PARAMETERS	End of SOM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of SOMA
GROUP	15	SOMA_PARAMETERS	Beginning of SOMA parameters group
INCLINATION_ANGLE	11		Inclination of orbit at ascending node
LONGITUDE_OF_ASCENDING	11		Longitude of ascending orbit
SATELLITE_REVOLUTION			Period of satellite revolution in minutes
LANDSAT_RATIO			Ratio to compensate for northern end of orbit
PATH_FLAG	1	= 0 or 1	End of path flag for Landsat
END_GROUP	15	SOMA_PARAMETERS	End of SOMA parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of SOMB
GROUP	15	SOMB_PARAMETERS	Beginning of SOMB parameters group
LANDSAT_NUMBER	1		Number of the Landsat satellite
PATH	3	= 1 to 233	Path number the satellite was on
END_GROUP	15	SOMB_PARAMETERS	End of SOMB parameters group

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of STRG
GROUP	15	STRG_PARAMETERS	Beginning of STRG parameters group
LONGITUDE_OF_CENTER	12	= -180.0 to +180.0	Longitude of center of projection
LATITUDE_OF_CENTER	11	= -90.0 to +90.0	Latitude of center of projection
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for STRG projection
END_GROUP	15	STRG_PARAMETERS	End of STRG parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of TM
GROUP	13	TM_PARAMETERS	Beginning of TM parameters group
SCALE_FACTOR_AT_CENTRAL_MERIDIAN	11	= 0.0 to 2.0	Scale factor at central meridian
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for TM projection
END_GROUP	13	TM_PARAMETERS	End of TM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of UTM
GROUP	14	UTM_PARAMETERS	Beginning of UTM parameters group
ZONE_NUMBER	3	= 1 to 60 or -1 to -60	Value used to indicate zone number
END_GROUP	13	UTM_PARAMETERS	End of UTM parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of VDGR
GROUP	15	VDGR_PARAMETERS	Beginning of VDGR parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian

Parameter Name	Size*	Value, Format, Range, and Units	Parameter Description/Remarks
LATITUDE_OF_PROJECTION_ORIGIN	11	= -90.0 to +90.0	Latitude of projection origin
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for EQC projection
END_GROUP	15	VDGR_PARAMETERS	End of VDGR parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of WIV
GROUP	14	WIV_PARAMETERS	Beginning of WIV parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for WIV projection
END_GROUP	14	WIV_PARAMETERS	End of WIV parameters group
Projection parameters data (not a Level 1 metadata parameter)			The following parameters are included only with products that select a map projection of WVII
GROUP	15	WVII_PARAMETERS	Beginning of WVII parameters group
LONGITUDE_OF_CENTRAL_MERIDIAN	12	= -180.0 to +180.0	Longitude of central meridian
FALSE_EASTING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False easting
FALSE_NORTHING	18	= -1.0×10^8 to $+1.0 \times 10^8$	False northing
FALSE_EASTING_NORTHING_UNITS	6	= "meters" or "feet"	Units for false easting and northing for MOLL projection
END_GROUP	15	WVII_PARAMETERS	End of WVII parameters group
END_GROUP	148	L1_METADATA_FILE	End of Level 1 metadata file level group
END			Required standalone parameter signifying file end
*ASCII bytes			

Table 3-14. Level 1 Metadata File

3.3.3 Ancillary Data Files

3.3.3.1 Internal Calibrator (IC) Data Files

The IC data files are included with the L1R output product only. The IC data for format 1 consist of scan-line-ordered internal lamp and shutter data for bands 1 through 5 and black-body radiance and shutter data for band 6L. IC data for format 2 consist of scan-

line-ordered internal lamp and shutter data for bands 7 and 8 and black-body radiance and shutter data for band 6H. The data are collected once per scan and are structured in a band sequential format in detector descending order. The IC data format 1 file is provided with products that include bands 1 through 6 low gain image data; the format 2 file is provided with products that include bands 6 high gain through 8. These data are subset to correspond to the user-requested product (i.e., by band and product size).

3.3.3.2 Mirror Scan Correction Data (MSCD) File

The consensus MSCD data file is included with the L1R output product only. Each logical record consists of three data values—the first half scan error, the second half scan error, and the scan line direction, along with scan quality information. This information, which usually applies to the previous scan, is used to compute deviations from nominal scan mirror profiles as measured on the ground and reported in the CPF. One consensus MSCD file is provided. A consensus MSCD file is a single MSCD file, created from the two original files included with the L0Rp product, with errors corrected according to L1 processing algorithms. These data are subset to correspond to the user-requested product size. Applicable Document 4 (see References) describes the file structure for the consensus MSCD, with the exception of the L1-assigned Vdata Name and Vdata Class, which are described below.

Vdata Name: L71ppprrr_rrrYYYYMMDD.MSD
Vdata Class: LPGS_MSCD

3.3.3.3 Payload Correction Data (PCD) File

The consensus PCD data file is included with the L1R output product only. This file consists of attitude and ephemeris profiles and high-frequency jitter measurements. One consensus PCD file is provided. A consensus PCD file is a single PCD file created from the two original files included with the L0Rp product, with errors corrected according to L1 processing algorithms. This consensus PCD file is not subsetting. Applicable Document 4 (see References) describes the file structure for the consensus PCD, with the exception of the L1-assigned Vdata Name and Vdata Class, which are described below.

Vdata Name: L71ppprrr_rrrYYYYMMDD.PCD
Vdata Class: LPGS_PCD

3.3.3.4 Scan Line Offsets

The scan line offsets are included with the L1R output product only. The scan line offsets represent the actual starting and ending pixel positions for valid (nonzero fill) Earth image data on a data-line-by-data-line basis. The scan line offset format 1 file is provided with products that include bands 1 through 6 low image data; the format 2 file is provided with products that include bands 6 high through 8. These data are subsetting to correspond to the user-requested product (i.e., by band and product size). Applicable Document 4 (see References) describes the file structure for the scan line offset, with the exception of the L1-assigned Vdata Name and Vdata Class, which are described below.

Vdata Name: L7fppprrr_rrrYYYYMMDD.ONN
Vdata Class: LPGS_SLO

3.3.3.5 Calibration Parameter File (CPF)

The CPF is a formatted file containing radiometric and geometric processing parameters required for L1 processing. It is provided with the L1R product only, without modification from the L0Rp product file. A complete description of this file currently exists in the Landsat 7 System Calibration Parameter File Definition (see References).

3.3.3.6 Geolocation Table File

The geolocation table file contains scene corner coordinates and their product-specific scan line numbers and is included with the L1R product only. Applicable Document 4 (see References) describes the file structure for the geolocation table, with the exception of the L1-assigned Vdata Name and Vdata Class, which are described below.

Vdata Name: L71ppprrr_rrrYYYYMMDD.GEO
Vdata Class: Index

3.3.3.7 LPS Metadata File

The LPS metadata files are included with the L1R output product without modification from with the L0Rp product. The metadata format 1 and format 2 files are provided with all L1R products. Some information in the LPS metadata file pertains to parent subintervals of the L1 product and may not be applicable to L1 products. Applicable Document 4 (see References) describes the file structure for the LPS metadata, with the exception of the L1-assigned Vdata Name, which is described below.

Vdata Name: L7fppprrr_rrrYYYYMMDD.MTA

3.3.4 Gap Mask

Please see Section 3.1.4 for the Gap Mask description.

3.4 NLAPS Data Format (NDF)

3.4.1 Level 1 Image File

Each Earth image band in the requested product is contained in a separate file. The data are laid out in a scan line sequential format in descending detector order (i.e., detector 16 is followed by detector 15 and so forth for the 30-m bands). The L1G image is radiometrically corrected and resampled for geometric correction and registration to geographic map projections.

3.4.2 Header File

The Image Header File contains information describing image data. The header file is an ASCII text file. Information in the header file consists of keyword/value entries in the following format: <keyword> = <value1> [, <value2>, <value3>, ..., <valueN>];

The characters "," and ";" serve as value and entry delimiters, respectively, whereas "=" separates the keyword field from value field(s). These special characters are not to be used in keyword and value fields. In rare instances when these special characters are required in keyword and value fields, the desired field must be enclosed in double quotes (i.e., "<field>", where <field> contains the above-mentioned special character[s]).

In the rare event that the double quote character is required in a field, it is represented by a backslash, followed by a double quote (e.g., "\""). A backslash in a field is denoted by two consecutive backslashes (e.g., "\\").

The first and last characters of keywords and values are non-blank characters. <Keywords> are unique and are single tokens. Words in keyword fields are connected by underscores. An example of a keyword is "BITS_PER_PIXEL."

Where possible, each entry in the <value> field is a single token. The keyword in the first entry of the header is "NDF_REVISION." All other header entries can appear in any order, except for the keyword "END_OF_HDR," which has no parameters and represents the end of a header. A semicolon also terminates this entry.

Each keyword starts at the beginning of a new line. Any number, including zero, or white spaces may appear outside of the keyword and value fields. White spaces refer to space, tab, Carriage-Return (CR), and Line-Feed (LF) characters.

Only required parameters are entered in the file. Those parameters that are not required may not be included. For example, NDF files containing mosaicked DEM data do not have BAND1-RADIOMETRIC_GAINS/BIAS entries. A parameter with a specified default value may not be included if it is to take on its default value.

Within the parameter tables, the following notations are used:

- <type> specifies the type or format of data to be used as a keyword value
- [optional type] specifies the type or format of optional data for a keyword value
- | represents "or" and is used for specifying alternative keyword values
- "<character>" specifies that the <character> must be included as part of the keyword value or value list, and the character set includes _ , / = ; .

KEYWORD	DESCRIPTION
NDF_REVISION	Format version code <m>".<nn> This document describes version "2.00"
DATA_SET_TYPE	Type of data Format of data type: <company>"_<sensor> <data type>[FMT<nnn>] Valid types are "EDC_MSS," "EDC_TM," "EDC_ETM+," and "NLAPS_DEM"
PRODUCT_NUMBER	Product order number in <NNNYMMDDSSSSdddd> format with NNN = node, YY = year, MM = month, DD = day, SSSS = sequence number, and dddd = unit number
PIXEL_FORMAT	Format of pixel

KEYWORD	DESCRIPTION
	Valid values are "BIT," "BYTE," "2BYTEINT," "4BYTEINT," "REAL," "DOUBLE" Note: Integers may be signed or unsigned
PIXEL_ORDER	Valid values are "NOT_INVERTED," "[<n>-]BYTE_INVERTED," "[<n>-]BIT_INVERTED" Example: "BYTE_INVERTED" Default value: "NOT_INVERTED"
BITS_PER_PIXEL	Number of bits per pixel Integer format
PIXELS_PER_LINE	Number of pixels per line Integer format
LINES_PER_DATA_FILE	Number of data lines for each data/image file Example: For a 3-band BIL imagery data file, the value of LINES_PER_DATA_FILE equals the number of lines in each band multiplied by 3 Integer format For BSQ imagery, the value of LINES_PER_DATA_FILE equals the number of lines in each band
DATA_ORIENTATION	Data orientation in <position>/"<direction> format Valid values: "UPPER_LEFT/RIGHT," "UPPER_LEFT/BOT," "UPPER_RIGHT/LEFT," "UPPER_RIGHT/BOT," "BOTTOM_LEFT/RIGHT," "BOTTOM_LEFT/TOP," "BOTTOM_RIGHT/LEFT," "BOTTOM_RIGHT/TOP"
NUMBER_OF_DATA_FILES	Total number of image/data files Header, work order report, and history files are excluded Integer format
DATA_FILE_INTERLEAVING	Interleaving type Valid values "BSQ"
TAPE_SPANNING_FLAG	Tape spanning flag for images that span multiple volumes in <n>/"<m> format, where <n> is the current volume number and <m> is the total number of volumes
START_LINE_NUMBER	First data/image line number on this volume (for multiple volumes) Integer format
START_DATA_FILE	First data file number on this volume (for multiple volumes) Integer format
LINES_PER_VOLUME	Number of data lines on this volume (for multiple volumes) Integer format
BLOCKING_FACTOR	Blocking factor Number of data records per block Integer format Default: "1"
RECORD_SIZE	Length of physical record in bytes Integer format
UPPER_LEFT_CORNER	<Longitude> ", " <Latitude> ", " <Easting> ", " <Northing>, where longitude and latitude represent geodetic coordinates in <DDMMSS>".<SSSSC> format with DDD = degrees, MM = minutes, SS.SSSS = seconds, and C = "N," "S," "E," or "W" Easting and northing are expressed in meters, in F13.3 format These four measurements are taken at the center of the upper-left-most pixel Example of longitude: 5 degrees, 13 min., 12.7 sec. west of prime meridian is expressed as "0051312.7000W" Example of latitude: 18 degrees, 12 min., 54.7 sec. north of the

KEYWORD	DESCRIPTION
	equator is expressed as "0181254.7000N"
UPPER_RIGHT_CORNER	<Longitude> "," <Latitude> "," <Easting> "," <Northing> Format is similar to that of UPPER_LEFT_CORNER These four measurements are taken at the center of the upper-right-most pixel
LOWER_RIGHT_CORNER	<Longitude> "," <Latitude> "," <Easting> "," <Northing> Format is similar to that of UPPER_LEFT_CORNER These four measurements are taken at the center of the lower-right-most pixel
LOWER_LEFT_CORNER	<Longitude> "," <Latitude> "," <Easting> "," <Northing> Format is similar to that of UPPER_LEFT_CORNER These four measurements are taken at the center of the lower-left-most pixel
REFERENCE_POINT	Valid values: "SCENE_CENTER", "NONE"
REFERENCE_POSITION	<Longitude> "," <Latitude> "," <Easting> "," <Northing> "," <Pixel #> "," <Line #> Used to geographically reference the image to the ground The longitude, latitude, easting, and northing formats are the same as those in UPPER_LEFT_CORNER Pixel # and Line # refer to reference point pixel and line numbers, respectively, with the first pixel in the image being 1,1 They both have F9.2 formats and can be negative Integer line/pixel numbers correspond to the center of a pixel
REFERENCE_OFFSET	<x-offset> "," <y-offset> Horizontal offset of the true reference point from the nominal WRS scene center in units of whole pixels Both are F9.2 format
ORIENTATION	Orientation angle in degrees measured clockwise from grid (map) north May be negative F11.6 format
MAP_PROJECTION_NAME	Map projection name, as specified in GCTP documentation
USGS_PROJECTION_NUMBER	USGS supported projection number, as specified in GCTP documentation
USGS_MAP_ZONE	USGS map zone code, for UTM and State Plan Cartographic System (negative numbers are used to indicate southern hemisphere for UTM zone)
USGS_PROJECTION_PARAMETERS	USGS map projection parameters There are 15 parameters, all with the same format (D26.15)
HORIZONTAL_DATUM	Name of the horizontal datum used Valid values: "NAD27," "NAD83," "WGS84," "ELLIPSOID" See Appendix 6
EARTH_ELLIPSOID_SEMI-MAJOR_AXIS	Semi-major axis of Earth ellipsoid F11.3 format, in meters
EARTH_ELLIPSOID_SEMI-MINOR_AXIS	Semi-minor axis of Earth ellipsoid F11.3 format, in meters
EARTH_ELLIPSOID_ORIGIN_OFFSET	<x-offset> "," <y-offset> "," <z-offset> x-, y-, and z-offsets of Earth ellipsoid in meters F11.3 format
EARTH_ELLIPSOID_ROTATION_OFFSET	<x-plane offset> "," <y-plane offset> "," <z-plane offset> Angular offset from x-plane, y-plane, and z-plane of Earth ellipsoid in degrees F9.6 format
WRS	WRS Path/Row in <ppp>"/"<rrr.n> format, where n is the fractional row

KEYWORD	DESCRIPTION
	value
ACQUISITION_DATE/TIME	UTC date and time of acquisition of reference point in ISO-compliant format: YYYY-MM-DDThh:mm:ssZ ©
SATELLITE	Satellite number Valid values: "LANDSAT_"<m>, where m is an integer 1-5 or 7
SATELLITE_INSTRUMENT	Instrument type: <SSSSSS>, where <SSSSSS> is the sensor type Valid values: "MSS," "TM," and "ETM+"
PRODUCT_SIZE	Valid values: "FULL_SCENE," "SUBSCENE," "MULTI_SCENE"
PIXEL_SPACING	<Horizontal pixel size> ", <vertical pixel size> Horizontal and vertical pixel size in PIXEL_SPACING_UNITS F9.4 format
PIXEL_SPACING_UNITS	Units of measure: "METERS"
PROCESSING_LEVEL	Processing level For ETM+, TM, and MSS, valid values are "01," "02," "03," "04," "05," "06," "07," "08," "09," "10" These correspond to the standard Landsat processing levels
RESAMPLING	Resampling kernel Valid values: "NN," "BL," "CC," "KD16," "SINC8," "SINC16," "NONE," <user-defined>, where <user-defined> is an unique name for a user-definable kernel
PROCESSING_DATE/TIME	Processing date.time in ISO-compliant format: YYYY-MM-DDThh:mm:ss In local system time ©
PROCESSING_SOFTWARE	Processing software version: "NLAPS_"<xx>," where xx = software version number
SUN_ELEVATION	Sun elevation in degrees at the reference point (acquisition time) F6.2 format
SUN_AZIMUTH	Sun azimuth in degrees at the reference point (acquisition time) F6.2 format
NUMBER_OF_BANDS_IN_VOLUME	Number of bands in the volume Integer format

Table 3-15. Header File Parameters

3.4.3 Level 1 Metadata File

Please see Section 3.3.2 for L1 Metadata File details.

3.4.4 Gap Mask

Please see Section 3.1.4 for Gap Mask details.

3.4.5 Work Order Report File

The Work Order Report File provides a record of the work executed into a DORRAN Product Order. This file is in ASCII format and contains information relative to the processing performed and the parameters used (e.g., latitudes and longitudes specified in degrees and heights specified in meters).

The Correction Processing Report File provides a record of the work executed in response to a DORRAN Product Order. It is in ASCII format for easy readability and contains the following information (notes describing units and/or formats are used for latitude, longitude, heights, dates, etc.):

- Product order information
- Processing stage reports
 - Name of processing stage
 - Start and completion date/time of processing stage
 - Summary/status information
- Processing stages may include
 - Ingest
 - Precision Modeling
 - DEM Ingest
 - DEM Processing
 - Apply Despiking Filter
 - Apply Deband Filter
 - Image Correction
 - Geometric Quality Assessment
 - Radiometric Quality Assessment
 - Product Formatting
- Summary Information (e.g., Work Order start and stop date/times and total CPU time)

NLAPS CORRECTION PROCESSING REPORT (Example)

NLAPS Version: 4_3_00e14
 Work Order: 011040402008500001 Priority: 9
 Satellite: Landsat-7 Sensor: ETM+
 Camera Number: N/A Sensor Mode: N/A

Input Data Ident: /diskIngest2/temp/011040402008500001/L71EDC1102226
 Input Media Type: Disk File Number: N/A
 Orbit Number: 98151

Processing Level: Systematic Geocorrection Resampling: CC
 Map Projection: UTM Zone: 18
 Earth Ellipsoid: NAD83 Panel Effect: FALSE
 Product Orient.: Satellite

Projection Params:
 6.378137000000000e+06 6.356752314140000e+06 0.000000000000000e+00
 0.000000000000000e+00 0.000000000000000e+00 0.000000000000000e+00
 0.000000000000000e+00 0.000000000000000e+00 0.000000000000000e+00
 0.000000000000000e+00 0.000000000000000e+00 0.000000000000000e+00
 0.000000000000000e+00 0.000000000000000e+00 0.000000000000000e+00
 Line Spacing: 030.0 Pixel Spacing: 030.0

Path/Strip no.: 014 Start Row no.: 029.0
 End Row no.: N/A

Image Lines: 6000 Image Pixels: 6493

Image Orientation: 10.46 deg from N Output Bands: 123456789
Viewing Angle: 0.04 deg

Scene center lat: 44.606 deg Scene center long: -73.516 deg
Sun Elevation: 54.09 deg Sun Azimuth: 139.84 deg
Scene center date: 2002 08 14 Scene center time: 15:26:51.9275

Output Media: Disk Output Product Id: N/A
Product Format: NDF Interleaving : BSQ
Catalogued: FALSE

Completion date: 2004 04 07 Completion time: 10:59:52

Termination Status: Successful Completion

=====

DETAILED PROCESSING RESULTS

=====

=====

RADIOMETRIC CORRECTION

=====

Algorithm: NASA

Band	Ref	DN to Radiance	Default
	Detector	gain offset	Abs Calib?
1	15	0.778740 -6.97873	FALSE
2	12	0.798819 -7.19882	FALSE
3	8	0.621653 -5.62164	FALSE
4	7	0.969291 -6.06931	FALSE
5	14	0.126220 -1.12622	FALSE
6	8	0.067087 -0.06708	FALSE
7	10	0.043898 -0.39389	FALSE
8	27	0.975591 -5.67560	FALSE
9	8	0.037205 3.162800	FALSE

Band 1 Coefficients (Qcal = (Q - offset) / gain):

Gain Mode: HIGH

Detector	Forward	Backward
	gain offset gain offset	
1	0.960342 6.911600	0.960342 6.906810
2	0.950054 7.094850	0.950054 7.090060
3	0.950495 6.740320	0.950495 6.735530
4	0.951127 6.574330	0.951127 6.569540
5	0.948987 6.653630	0.948987 6.648840
6	0.952194 6.498690	0.952194 6.493900
7	0.962207 6.228640	0.962207 6.223850
8	0.960842 6.117060	0.960842 6.112280
9	0.957314 6.066810	0.957314 6.062020

10		0.957566	5.990210	0.957566	5.985420
11		0.958945	6.083820	0.958945	6.079030
12		0.949041	6.329580	0.949041	6.324790
13		0.955021	6.502640	0.955021	6.497850
14		0.943699	6.743620	0.943699	6.738830
15		0.953371	6.724250	0.953371	6.719460
16		0.954400	6.630990	0.954400	6.626210

Band 2 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: HIGH

Detector		Forward		Backward	
		gain	offset	gain	offset

1		0.938977	6.804560	0.938977	6.794900
2		0.949396	6.920310	0.949396	6.910650
3		0.944009	7.010020	0.944009	7.000360
4		0.950580	6.783130	0.950580	6.773470
5		0.946023	6.838120	0.946023	6.828450
6		0.948274	6.569570	0.948274	6.559910
7		0.969289	6.107580	0.969289	6.097910
8		0.949267	6.283690	0.949267	6.274020
9		0.951517	6.304300	0.951517	6.294640
10		0.956479	6.160860	0.956479	6.151200
11		0.956445	6.198250	0.956445	6.188590
12		0.951680	6.352280	0.951680	6.342620
13		0.959374	6.442400	0.959374	6.432740
14		0.941859	6.725560	0.941859	6.715900
15		0.950497	6.748920	0.950497	6.739260
16		0.954122	6.620250	0.954122	6.610590

Band 3 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: HIGH

Detector		Forward		Backward	
		gain	offset	gain	offset

1		0.949206	6.226510	0.949206	6.220700
2		0.943181	6.432940	0.943181	6.427130
3		0.952270	6.269500	0.952270	6.263690
4		0.951920	6.134450	0.951920	6.128640
5		0.959897	5.942650	0.959897	5.936840
6		0.950786	5.930450	0.950786	5.924640
7		0.962914	5.731090	0.962914	5.725280
8		0.953018	5.876670	0.953018	5.870860
9		0.961008	5.718920	0.961008	5.713110
10		0.971431	5.582900	0.971431	5.577090
11		0.969670	5.563450	0.969670	5.557640
12		0.956630	5.878110	0.956630	5.872300
13		0.954672	6.059720	0.954672	6.053910
14		0.950138	6.240570	0.950138	6.234760
15		0.950500	6.094960	0.950500	6.089150

16 | 0.956894 6.032850 0.956894 6.027040

Band 4 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: LOW

Detector	Forward		Backward	
gain	offset	gain	offset	
1	0.976442	3.720750	0.976442	3.717350
2	0.957020	4.007190	0.957020	4.003790
3	0.966064	3.901490	0.966064	3.898090
4	0.964053	3.792050	0.964053	3.788660
5	0.965949	3.866010	0.965949	3.862620
6	0.957106	3.893960	0.957106	3.890560
7	0.965585	3.907260	0.965585	3.903870
8	0.958357	4.108360	0.958357	4.104960
9	0.974503	3.687160	0.974503	3.683770
10	0.964873	4.039750	0.964873	4.036360
11	0.968608	3.921370	0.968608	3.917980
12	0.971872	3.793350	0.971872	3.789950
13	0.956386	3.873310	0.956386	3.869920
14	0.975008	3.590030	0.975008	3.586640
15	0.968432	3.918960	0.968432	3.915570
16	0.972345	3.802490	0.972345	3.799090

Band 5 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: HIGH

Detector	Forward		Backward	
gain	offset	gain	offset	
1	0.956878	6.845350	0.956878	6.846000
2	0.952391	6.580580	0.952391	6.581230
3	0.953862	6.532760	0.953862	6.533410
4	0.948992	6.581110	0.948992	6.581770
5	0.950334	6.656560	0.950334	6.657210
6	0.957422	6.291610	0.957422	6.292260
7	0.969421	6.152000	0.969421	6.152650
8	0.963388	6.262720	0.963388	6.263370
9	0.963532	6.283690	0.963532	6.284340
10	0.955747	6.487410	0.955747	6.488060
11	0.958770	6.043970	0.958770	6.044620
12	0.965507	6.331850	0.965507	6.332500
13	0.957685	6.478740	0.957685	6.479390
14	0.960680	6.491520	0.960680	6.492170
15	0.957745	6.694090	0.957745	6.694740
16	0.954045	6.535280	0.954045	6.535930

Band 6 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: LOW

Detector	gain	Forward offset	gain	Backward offset
1	0.870418	25.57510	0.870418	25.57510
2	0.886202	23.79930	0.886202	23.79930
3	0.866645	25.77130	0.866645	25.77130
4	0.866342	25.80510	0.866342	25.80510
5	0.848437	27.61710	0.848437	27.61710
6	0.888179	23.53360	0.888179	23.53360
7	0.844112	28.16340	0.844112	28.16340
8	0.829109	29.72180	0.829109	29.72180

Band 7 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: HIGH

Detector	gain	Forward offset	gain	Backward offset
1	0.952655	6.607460	0.952655	6.604560
2	0.951307	6.762070	0.951307	6.759170
3	0.967407	6.496610	0.967407	6.493710
4	0.934655	6.813100	0.934655	6.810200
5	0.956428	6.686220	0.956428	6.683320
6	0.969594	6.414570	0.969594	6.411660
7	0.958988	6.596020	0.958988	6.593120
8	0.957245	6.639880	0.957245	6.636980
9	0.957737	6.616630	0.957737	6.613720
10	0.963618	6.555470	0.963618	6.552560
11	0.962342	6.487730	0.962342	6.484820
12	0.963907	6.376260	0.963907	6.373360
13	0.952484	6.762800	0.952484	6.759900
14	0.960749	6.572720	0.960749	6.569810
15	0.952178	6.596520	0.952178	6.593620
16	0.953834	6.589930	0.953834	6.587030

Band 8 Coefficients ($Q_{cal} = (Q - \text{offset}) / \text{gain}$):

Gain Mode: LOW

Detector	gain	Forward offset	gain	Backward offset
1	0.964709	2.826960	0.964709	2.845710
2	0.970803	2.785030	0.970803	2.803780
3	0.972036	2.743200	0.972036	2.761950
4	0.970357	2.834090	0.970357	2.852840
5	0.958969	2.972800	0.958969	2.991550
6	0.964357	2.759510	0.964357	2.778260
7	0.961783	2.925370	0.961783	2.944120
8	0.972680	2.798340	0.972680	2.817090
9	0.957847	2.806570	0.957847	2.825320
10	0.965939	2.875220	0.965939	2.893970

11		0.962840	2.684110	0.962840	2.702860
12		0.966757	2.760600	0.966757	2.779350
13		0.965707	2.622820	0.965707	2.641570
14		0.971471	2.631110	0.971471	2.649860
15		0.956927	2.788130	0.956927	2.806880
16		0.969073	2.812460	0.969073	2.831210
17		0.969899	2.722760	0.969899	2.741510
18		0.959891	2.720960	0.959891	2.739710
19		0.962085	2.720210	0.962085	2.738960
20		0.965646	2.895460	0.965646	2.914210
21		0.957737	2.705020	0.957737	2.723770
22		0.961982	2.868510	0.961982	2.887260
23		0.956571	2.875140	0.956571	2.893890
24		0.955884	3.019800	0.955884	3.038560
25		0.970123	2.863860	0.970123	2.882610
26		0.961514	2.848950	0.961514	2.867700
27		0.968385	2.906220	0.968385	2.924970
28		0.963180	2.969760	0.963180	2.988510
29		0.967447	2.881960	0.967447	2.900710
30		0.957820	2.913660	0.957820	2.932410
31		0.970579	2.740050	0.970579	2.758800
32		0.959493	2.841540	0.959493	2.860290

Band 9 Coefficients (Qcal = (Q - offset) / gain):

Gain Mode: HIGH

Detector		Forward		Backward	
		gain	offset	gain	offset

1		0.947788	2.699390	0.947788	2.699390
2		0.963305	0.934474	0.963305	0.934474
3		0.939856	3.345010	0.939856	3.345010
4		0.940573	3.112050	0.940573	3.112050
5		0.922160	5.059160	0.922160	5.059160
6		0.968277	0.278725	0.968277	0.278725
7		0.914321	6.026500	0.914321	6.026500
8		0.897260	7.725360	0.897260	7.725360

=====

DEM PROCESSING

Elevation Correction Applied: None

=====

RADIOMETRIC QUALITY ASSESSMENT

NOTE:

Mean, Std.Dev, Striping are in DN's (Digital Numbers).

Band	Chip Location Line Pixel	Chip Size Lines Pixels	Mean	Std Dev	Striping
1	1197.60	1268.00 128 128	101.33	1.531	0.0812
1	2394.20	2535.00 128 128	83.59	0.670	0.0582
1	3590.80	3802.00 128 128	95.35	0.585	0.0615
1	4787.40	5069.00 128 128	82.55	0.452	0.0663
2	1197.60	1268.00 128 128	74.63	2.158	0.1624
2	2394.20	2535.00 128 128	60.67	0.381	0.0851
2	3590.80	3802.00 128 128	63.76	0.506	0.1104
2	4787.40	5069.00 128 128	57.97	0.337	0.0749
3	1197.60	1268.00 128 128	62.47	3.483	0.2812
3	2394.20	2535.00 128 128	45.47	0.577	0.1072
3	3590.80	3802.00 128 128	50.61	0.570	0.0931
3	4787.40	5069.00 128 128	43.27	0.435	0.1155
4	1197.60	1268.00 128 128	94.72	12.800	1.1561
4	2394.20	2535.00 128 128	97.79	2.287	0.1293
4	3590.80	3802.00 128 128	20.81	0.582	0.0597
4	4787.40	5069.00 128 128	96.79	2.788	0.2992
5	1197.60	1268.00 128 128	92.25	4.370	0.3518
5	2394.20	2535.00 128 128	77.51	2.278	0.3962
5	3590.80	3802.00 128 128	16.54	0.501	0.1131
5	4787.40	5069.00 128 128	72.43	1.233	0.1374
6	599.20	634.40 128 128	137.22	1.435	0.0872
6	1197.40	1267.80 128 128	134.95	1.371	0.1068
6	1795.60	1901.20 128 128	128.01	0.640	0.0911
6	2393.80	2534.60 128 128	132.40	0.397	0.0545
7	1197.60	1268.00 128 128	45.98	4.676	0.4085
7	2394.20	2535.00 128 128	34.81	1.049	0.1295
7	3590.80	3802.00 128 128	13.76	0.552	0.0429
7	4787.40	5069.00 128 128	32.09	0.605	0.0810
8	2394.40	2536.80 128 128	72.69	2.105	0.1232
8	4787.80	5072.60 128 128	62.70	0.970	0.1193
8	7181.20	7608.40 128 128	51.94	2.993	0.2572
8	9574.60	10144.20 128 128	65.19	1.088	0.1292
9	599.20	634.40 128 128	160.83	2.589	0.1269
9	1197.40	1267.80 128 128	156.77	2.398	0.1775
9	1795.60	1901.20 128 128	144.03	1.142	0.1157
9	2393.80	2534.60 128 128	152.35	0.671	0.0941

PRODUCT FORMATTING

Product Scene Center Location (lat/long) : 44.606 -73.516
Product Scene Center Date/Time (yyyy mm dd): 2002 8 14 15:26:51.9275

Product Extent:

Lat: 45.57	Lat: 45.22
Long: -74.51	Long: -72.07
North: 5046390.96	North: 5011043.46
East: 538302.56	East: 729828.04

Lat: 43.98	Lat: 43.63
Long: -74.93	Long: -72.56
North: 4869409.85	North: 4834062.35
East: 505639.33	East: 697164.82

EXECUTION INFORMATION

Stage	Start	End	CPU
Ingest	Wed Apr 7 10:36:25 2004	Wed Apr 7 10:40:44 2004	137.74
ImCorr	Wed Apr 7 10:41:07 2004	Wed Apr 7 10:58:31 2004	1366.28
RadQa	Wed Apr 7 10:58:32 2004	Wed Apr 7 10:58:33 2004	0.67
Output	Wed Apr 7 10:58:36 2004	Wed Apr 7 10:59:46 2004	16.50
Catalog	Wed Apr 7 10:59:46 2004	Wed Apr 7 10:59:47 2004	0.61
-----			1521.80

3.4.6 History Processing Parameters File

See References (Document 7) for a detailed file format description.

3.4.7 DEM Header File (Optional)

The DEM Header File contains information that describes image data. The header file is an ASCII text file. Header examples are listed below to demonstrate how the metadata appear in the first file of each digital product.

3.4.7.1 ETM+ NLAPS DEM Header Example

```

NDF_REVISION=2.00;
DATA_SET_TYPE=NLAPS_DEM;
PRODUCT_NUMBER=ndfetm;
PIXEL_FORMAT=2BYTEINT;
PIXEL_ORDER=NOT_INVERTED;
BITS_PER_PIXEL=16;
PIXELS_PER_LINE=9048;
LINES_PER_DATA_FILE=8577;
DATA_ORIENTATION=UPPER_LEFT/RIGHT;
NUMBER_OF_DATA_FILES=1;
DATA_FILE_INTERLEAVING=BSQ;
TAPE_SPANNING_FLAG=1/1;
START_LINE_NUMBER=1;
START_DATA_FILE=1;
LINES_PER_VOLUME=8577;
BLOCKING_FACTOR=1;

```

RECORD_SIZE=9048;
 UPPER_LEFT_CORNER=0990225.1489W,0424435.5517N,496700.000,4732300.000;
 UPPER_RIGHT_CORNER=0961642.3389W,0424239.1292N,722875.000,4732300.000;
 LOWER_RIGHT_CORNER=0962131.5257W,0404654.7399N,722875.000,4517900.000;
 LOWER_LEFT_CORNER=0990220.8586W,0404843.5776N,496700.000,4517900.000;
 REFERENCE_POINT=SCENE_CENTER;
 REFERENCE_POSITION=0974044.7685W,0414612.5447N,609787.500,4625100.000,4524.50,4289.00;
 REFERENCE_OFFSET=207.83,12.21;
 ORIENTATION=0.015359;
 MAP_PROJECTION_NAME=UTM;
 USGS_PROJECTION_NUMBER=1;
 USGS_MAP_ZONE=14;
 USGS_PROJECTION_PARAMETERS=0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000,0.000000000000000;
 HORIZONTAL_DATUM=WGS84;
 EARTH_ELLIPSOID_SEMI-MAJOR_AXIS=6378137.000;
 EARTH_ELLIPSOID_SEMI-MINOR_AXIS=6356752.314;
 EARTH_ELLIPSOID_ORIGIN_OFFSET=0.000,0.000,0.000;
 EARTH_ELLIPSOID_ROTATION_OFFSET=0.000000,0.000000,0.000000;
 PRODUCT_SIZE=FULL_SCENE;
 PIXEL_SPACING=25.0000,25.0000;
 PIXEL_SPACING_UNITS=METERS;
 RESAMPLING=BL;
 PROCESSING_DATE/TIME=1999-11-23T15:19:52;
 PROCESSING_SOFTWARE=NLAPS_4_1_0;
 NUMBER_OF_BANDS_IN_VOLUME=1;
 DEM_NAME=DEM;
 UNIT_OF_ELEVATION_MEASURE=METERS;
 VERTICAL_DATUM=SEA_LEVEL;
 END_OF_HDR;

3.4.8 DEM Data File (Optional)

The DEM Data File contains elevation samples. There are no header records within the files, nor are there any prefix and/or suffix data to the individual image records. The DEM Data File is in the same pixel spacing as the satellite data when all bands are the same resolution. The DEM Data File is of the same resolution as the reflective bands when satellite data is multi-resolution. The data file is 16-bits per pixel.

Section 4 Product Packaging

L1 products are available on DLT, CD-ROM, DVD-R, and via electronic transfer. The following sections provide information on each of the distribution methods for the available L1 product formats.

4.1 Digital Linear Tape (DLT)

Data products may be supplied on Digital Linear Tape (DLT). This includes a family of devices and media including DLT-IV, DLT8000, and SDLT. At this time, DLT-IV devices (DLT-7000) are no longer available from vendors. However, a large number of existing DLT-IV devices are in use. New tape devices include DLT8000 and Super DLT (SDLT). Both are “read compatible” with media written using DLT-IV devices.

Data are written using the UNIX tar (tape archive) utility format (per IEEE POSIX standard 1003.1), thus preserving directory structure and file names. The no-swap device and a fixed blocking factor of 256 512-byte blocks are used to maximize portability between platforms. The root directory must contain a README and summary file, which describes product content, and a set of files or subdirectories. Depending on the distribution technique, orders with only one scene may place all files in the root directory. However, if there are multiple scene units, there must be one subdirectory for each product ordered. Product subdirectories are labeled with a unique name and referenced in the summary file. All of the files associated with a product exist at a common level within the product subdirectory.

Product orders with large scenes or a number of scene units may exceed the capacity of the media. If this occurs, distribution systems span scene units across multiple volumes; a copy of the HDF directory file is included on all output volumes for user convenience. If a FAST-L7A product must be written to more than one DLT, relevant header records are replicated.

The DLT label includes the following information: Mission indicator (which is L7 or Landsat 7), start path, start row, end row, acquisition date, and product type (which is L0Rp), DLT format (e.g., DLT4000, DLT7000, DLT8000, SDLT), type of TAR used (e.g., IRIX, GNU), and the blocking factor.

4.2 CD-ROM

The CD-ROM format also contains the L1 volume descriptor (readme file) with the same file names as listed in the previous section. Only single-scene (or less) products are written to CD-ROM due to the size of the Band 8 file. If an HDF L1 product must be written to more than one CD, an HDF directory is written to each CD. If a FAST-L7A product must be written to more than one CD, relevant header records are replicated.

At least the following information is labeled directly onto the CD-ROM: product type (e.g., HDF, GeoTIFF, FAST, or NDF), DORRAN order number, DORRAN unit number, CD-ROM volume number, start path, start row, end row, acquisition date, and USGS

logo. The path, row, and acquisition date information is supplied in the format of the naming convention of the base part of file names as defined in Section 2.

4.3 DVD-R

Data products on DVD-R (Digital Video Disk write once) are mastered using ISO 9660 Interchange Level 2, the international standard for file formatting a DVD-R. Rock Ridge and Joliet extensions are present on the CD-ROM. No file unpacking is required. The files are ready for processing using HDF or other software tools. DVD-R products are mastered using single-sided, single-layered technology, providing a capacity of 4.7 gigabytes. This configuration is compatible with most DVD-ROM readers.

The root directory contains a README and summary file, which describes product content, and a set of files or subdirectories. Depending on the distribution technique, orders with only one scene may place all files in the root directory. However, if there are multiple scene units, there must be one subdirectory for each product ordered. Product subdirectories are labeled with a unique name and referenced in the summary file. All of the files associated with a product exist at a common level within the product subdirectory.

Product orders with large scenes or a number of scene units may exceed the capacity of the media. If this occurs, distribution systems span scene units across multiple volumes; a copy of the HDF directory file is included on all output volumes for user convenience. If a FAST-L7A product must be written to more than one DVD-R, relevant header records are replicated.

The DVD-R label includes the following information: order and unit number, scene identifiers (granule or entity ID), mission indicator (which is L7 or Landsat 7), start path, start row, end row, acquisition date, and product type.

4.4 Electronic Transfer

Products available via electronic transfer also include the L1 volume descriptor (readme file) with the same file names as listed above. Electronic data transfer uses UNIX FTP. File Transfer Protocol (FTP), as described in RFC 959, is an Internet standard for file transfers that supports retrieval of files from a remote server. This distribution method may not be available to all end users by all distribution systems. In some cases, special high-speed network requirements must be arranged. Various strategies and procedures to access data may vary significantly between distribution systems.

When FTP service is available, data are stored using the following standard. The home or initial login directory contains a set of files or subdirectories. Depending on the distribution technique, orders with only one scene may place all files in the home directory. However, if there are multiple scene units, there must be one subdirectory for each product ordered. The product subdirectories are labeled with a unique name. All of the files associated with a product exist at a common level within the product subdirectory.

The Bulk Processing Subsystem GZips (compresses) all Standard L1T scenes. Each individual file within the scene is GZipped.

Section 5 Software Tools

A variety of public domain software tools are available for processing the L1 distribution product in either an HDF or an independent computing environment.

5.1 NCSA HDF Libraries

HDF is a library- and platform-independent data format for the storage and exchange of scientific data. It includes Fortran and C calling interfaces and utilities for analyzing and converting HDF data files. HDF is developed and supported by the National Center for Supercomputing Applications (NCSA) and is available in the public domain.

The HDF library contains two parts: the base library and the multi-file library. The base library contains a general-purpose interface and application-level interfaces, one for each data structure type. Each application-level interface is designed specifically to read, write, and manipulate one type. The general-purpose interface contains functions such as file Input/Output (I/O), error handling, memory management, and physical storage. HDF library functions can be called from C or Fortran user application programs.

HDF source code for UNIX, Virtual Memory Storage (VMS), Windows NT/95, and Macintosh is available via anonymous FTP from <http://hdf.ncsa.uiuc.edu/obtain.html>. HDF reference manuals, user guides, release notes, and newsletters are Web accessible at <http://hdf.ncsa.uiuc.edu>.

5.2 HDF Libraries

HDF-EOS is standard HDF with EOS Data and Information System (EOSDIS) Core System (ECS) conventions and metadata added. The principal distinction is the specification of three geolocation data types: point, grid, and swath, which allow the file contents to be queried by Earth coordinates and time using the HDF Application Programming Interface (API). The LORp does not employ either of these data structures. However, any application that makes use of the HDF-EOS API does have, as a consequence of linking to the API, access to the NCSA native base libraries, which can be used to access the distribution OR product.

EOSView is a file-viewing tool developed for the ECS Project to examine and verify HDF data files. This tool enables users of Earth Observing System (EOS) data products to view the contents of HDF files and individual objects via straightforward product access and display tools.

Supported record types for viewing and display capability include images, multidimensional arrays, text, Vdata, and Vgroup. EOSView users see the underlying HDF structures and are prompted for the parts of the structure they wish to view. Users of the Landsat 7 OR product may also find the Science Data Production (SDP) Toolkit useful for follow-on processing. The SDP Toolkit consists of a set of fully tested and reliable C and Fortran language functions, customized for application to ECS product generation software. Of particular interest to L7 data users is the ODL parser,

which allows for reading, writing, and manipulating product metadata and the digital elevation model software tools.

The SDP Toolkit and HDF libraries are available via anonymous FTP from <ftp://edhs1.gsfc.nasa.gov>. Because this software was developed under a NASA contract and is intended for use by EOS instrument teams and science investigators, access to download it is password protected. The password may be obtained via e-mail sent to pgstlkit@eos.hitc.com.

5.3 ODL Parser

The ODL parser (Version 1.0) incorporated into the SDP Toolkit was originally implemented by the University of Colorado's Laboratory for Atmospheric and Space Physics (LASP). The Jet Propulsion Laboratory (JPL) enhanced the ODL parser in building its Planetary Data System. This enhanced version, available via anonymous FTP from <ftp://miranda.colorado.edu> (IP address: 128.128.137.33), was modified by IAS. LPGS uses this IAS-modified version.

The IAS-modified version should be particularly useful to those operating in a non-HDF-EOS environment. The software stands alone and can be used to read the LORp or L1 metadata external elements and the CPF.

Appendix A Projection Parameters

This appendix contains the map projection parameters used in the L1 FAST-L7A L1G products Note: * = NLAPS Only

Table A-1) and the USGS projection parameters (Table A-2 and A-3).

Project Name	Mnemonic
Alaska Conformal	AKC*
Albers Equal Area	AEA
Azimuthal	AZIM*
Equidistant Conic (Type A and B)	EQC*
Equirectangular	EQUI*
General Vertical Near Side Perspective	GVNP*
Gnomonic	GNOM*
Hammer	HAMM*
Interrupted Goodes Homolosine	IGH*
Interrupted Mollweide	IM*
Lambert Azimuthal Equal Area	LAEA*
Lambert Conformal Conic	LCC
Mercator	MERC*
Miller Cylindrical	MCYL*
Mollweide	MOLL*
Oblated Equal Area	OEA*
Oblique Mercator (Type A and B)	OM
Orthographic	ORTH*
Polar Stereographic	PS
Polyconic	PC
Robinson	ROBN*
Sinusoidal	SINU*
Space Oblique Mercator (Type A and B)	SOM
State Plane	STPL*
Stereographic	STRG*
Transverse Mercator (Gauss-Krueger)	TM
Universal Transverse Mercator	UTM
Van Der Grinten	VDGR*
Wagner IV	WIV*
Wagner VII	WVII*

Note: * = NLAPS Only

Table A-1. L1G Fast-L7A Projection Parameters

Projection Name Mnemonic	Array Element							
	1	2	3	4	5	6	7	8
AEA	SMajor	SMinor	Stdpr1	Stdpr2	CentMer	OriginLat	FE	FN
AKC	SMajor	SMinor					FE	FN
AZIM	Sphere				CentLon	CenterLat	FE	FN
EQCA	SMajor	SMinor	Stdpar		CentMer	OriginLat	FE	FN
EQCB	SMajor	SMinor	Stdpr1	Stdpr2	CentMer	OriginLat	FE	FN
EQUI	Sphere				CentMer	TrueScale	FE	FN
GNOM	Sphere				CentLon	CenterLat	FE	FN
GVNP	Sphere		Height		CentLon	CenterLat	FE	FN
HAMM	Sphere				CentMer		FE	FN
IGH	Sphere							
IM	Sphere							
LAEA	Sphere				CentLon	CenterLat	FE	FN
LCC	SMajor	SMinor	Stdpr1	Stdpr2	CentMer	OriginLat	FE	FN
MCYL	Sphere				CentMer		FE	FN
MERC	SMajor	SMinor			CentMer	TrueScale	FE	FN
MOLL	Sphere				CentMer		FE	FN
OEA	Sphere		Shapem	Shapen	CentLon	CenterLat	FE	FN
OMA	SMajor	SMinor	Factor			OriginLat	FE	FN
OMB	SMajor	SMinor	Factor	AziAng	AzmthPt	OriginLat	FE	FN
ORTH	Sphere				CentLon	CenterLat	FE	FN
PC	SMajor	SMinor			CentMer	OriginLat	FE	FN
PS	SMajor	SMinor			LongPol	TrueScale	FE	FN
ROBN	Sphere				CentMer		FE	FN
SINU	Sphere				CentMer		FE	FN
SOM	SMajor	SMinor	Satnum	Path			FE	FN
STPL								
STRG	Sphere				CentLon	CenterLat	FE	FN
TM	SMajor	SMinor	Factor		CentMer	OriginLat	FE	FN
UTM	Lon/Z	Lat/Z						
VDGR	Sphere				CentMer	OriginLat	FE	FN
WIV	Sphere				CentMer		FE	FN
WVII	Sphere				CentMer		FE	FN

**Table A-2. USGS Projection Parameters – Projection Transformation Package
Projection Parameters**

Projection Name Mnemonic	Array Element						
	9	10	11	12	13	14	15
AEA							
AKC							
AZIM							
EQCA							
EQCB							
EQUI							
GNOM							
GVNP							
HAMM							
IGH							
IM							
LAEA							
LCC							
MCYL							
MERC							
MOLL							
OEA	Angle						
OMA	Long1	Lat1	Long2	Lat2			
OMB					one		
ORTH							
PC							
PS							
ROBN							
SINU							
SOM					one		
STPL							
STRG							
TM							
UTM							
VDGR							
WIV							
WVII							

**Table A-3. USGS Projection Parameters – Projection Transformation Package
Projection Parameters Elements 9-15**

Where	Lon/Z	=	Longitude of any point in the UTM zone or zero
	Lat/Z	=	Latitude of any point in the UTM zone or zero
	SMajor	=	Semi-major axis of ellipsoid If zero, Clarke 1866 in m is assumed
	SMinor	=	If less than zero, eccentricity squared of the ellipsoid If zero, a spherical form is assumed If greater than zero, the semi-major axis of ellipsoid
	Sphere	=	Radius of the reference sphere If zero, 6370997 m is used
	Stdpar	=	Latitude of the standard parallel
	Stdpr1	=	Latitude of the first standard parallel
	Stdpr2	=	Latitude of the second standard parallel
	CentMer	=	Longitude of the central meridian
	OriginLat	=	Latitude of the projection origin
	FE	=	False easting in the same units as the semi-major axis
	FN	=	False northing in the same units as the semi-major axis
	LongPol	=	Longitude down below pole of map
	TrueScale	=	Latitude of true scale
	Factor	=	Scale factor at central meridian (TM) or center of projection (OMA/OMB)
	CentLon	=	Longitude of center of projection
	CenterLat	=	Latitude of center of projection
	Height	=	Height of perspective point
	Long1	=	Longitude of first point on center line
	Long2	=	Longitude of second point on center line
	Lat1	=	Latitude of first point on center line
	Lat2	=	Latitude of second point on center line
	AziAng	=	Azimuth angle east of north of center line
	AzmthPt	=	Longitude of point on central meridian where azimuth occurs
	Satnum	=	Landsat satellite number
	Path	=	Landsat path number (use WRS-1 for Landsat 1, 2, and 3 and WRS-2 for Landsat 4, 5, 6, or 7)
	Shapem	=	Oval shape parameter m
	Shapen	=	Oval shape parameter n
	Angle	=	Oval rotation angle

Table A-4. USGS Projection Parameters Key

Note: All array elements with blank fields are set to zero. All angles (latitudes, longitudes, azimuths, etc.) are entered in packed degrees/minutes/seconds (DDDDMMSS.SS) format.

References

See <http://landsat.usgs.gov/resources/acronyms.php> for a list of acronyms.

The following documents provide additional detail and reference information regarding the format of the L1 output files.

USGS/EROS. LS-DFCB-02. Landsat 7 ETM+ Level Zero-R Archive (L0Ra) DFCB. September 2004.

USGS/EROS. LS-DFCB-19. National Land Archive Production System (NLAPS) Systematic Format Description Document. July 2000.

USGS/EROS. IAS-207. Landsat 7 System Calibration Parameter File Definition. Revision 5. August 2005.

505-10-36. Earth Science Data and Information System (ESDIS) Project Mission Specific Requirements for the Landsat 7 Mission L1 Processing. November 1998.

GeoTIFF Specification. Revision 1.0.
<<http://www.remotesensing.org/geotiff/spec/geotiffhome.html>>.

Jet Propulsion Laboratory. California Institute of Technology. "Object Description Language Specification and Usage." Chapter 12 of Planetary Data System Standards Reference. Version 3.2. July 24, 1995.

National Land Archive Production System (NLAPS) Systematic Format Description Document – U.S. Geological Survey Format Specifications for Geometrically Corrected Landsat L1 Digital Data Products. July 2000.